



Rigid/IMC Conduit Fittings T&B Catalog Number:

3870-TB

UPC Number: 78621003870

Status: Active

Description:

1/2 in. Threaded insulated Grounding Bushing, Aluminum-Electro Zinc Plated, wire range-14-4, thermoplastic insulator. For use with Rigid/IMC Conduit.

Coriduit.	
Application	
	For quick installation of bonding jumper to multiple metal conduits (Rigid and IMC).
	Designed to bush conductors and prevent insulation damage.
General	
Trade Size (inches)	1/2
Material	Malleable Iron
Finish	Electro Zinc Plated
Wire Range	14-4
Dimension Information	
Bushing Diameter (inches)	1.125
Throat Diameter (inches)	0.56
Lug Length (inches)	1.31
Swing Radius (inches)	1.212
Bushing Height (inches)	0.657
Conduit Size (inches)	1/2
Specifications	
3dmodel	Available on Website
Packaging	
T&B Inner Pack	50
Package in Units	100
T&B Sold in UOM	Each
T&B Weight Per UOM	6 lbs. per 100
Application Support	
T&B Instruction Sheets	ta00375-tb2
Notes	
	Availabe with DURA-PLATE Finish
Certifications	
RoHS Compliance	No
Certifications	



File Nbr: E 3060



For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com