

## Flexible Conduits & Fittings T&B Catalog Number:

BVIVG-U187

UPC Number: 78620995056 Status: Active

**Description:** 

PMAFIX black female thread adapter with UNEF threads and O-ring. Material - polyamide 6, thread size - 3/4 in. -20, conduit size NW - 17.

| Δ | n | n | li | са | ti | ^ | n |
|---|---|---|----|----|----|---|---|
| _ | u | v |    |    | ш  | u |   |

| • •                                   |  |
|---------------------------------------|--|
|                                       | For use in machine, vehicle and traction building    |
| Characteristics                       |  |
|                                       | Very high impact resistance                          |
|                                       | Vibration proof connection to PMAFLEX conduits       |
|                                       | High conduit pull-out strength                       |
|                                       | Very good chemical properties                        |
|                                       | Self-extinguishing, free from halogens and cadmi-    |
|                                       | um   |
|                                       | Fits both conduit profiles - Fine (T) and coarse (G) |
| General                               |  |
| Material                              | Polyamide 6  |
| Color                                 | Black  |
| Thread Type                           | UNEF   |
| Compatiable With                      | PMAFLEX, PMA Smart Line                              |
| Dimension Information                 |  |
| Fits to Conduit Size (NW)             | 17   |
| Fits to Conduit Size (MW)             | 20   |
| Fits to Conduit Size (inches)         | 1/2  |
| Thread Length (mm)                    | 9.0  |
| Thread Size (UNEF)                    | 3/4" - 20  |
| Technical Information                 |  |
| Temperature Range-Continuous (Celsius | s) -40 degree C to +105 degree C                     |
| Temperature-Short-Term (Celsius)      | +160 degree C  |
| Technical Data Sheet                  | Available on Website                                 |
| Chemical Resistance Chart             | Available on Website                                 |
| IP Ratings                            |  |
| IP Rating                             | IP68 stat. / IP67 dyn.                               |
| Packaging                             | ii oo stat. / ii o'r dyff.                           |
|                                       | 500  |
| T&B Order Multiple                    | 500  |
| T&B Inner Pack                        | 50   |
| Package in Units                      | 250  |
| T&B Sold in UOM                       | Each Cod the Foot                                    |
| T&B Weight Per UOM                    | 0.04 lbs. Each                                       |
| Application Support                   |  |
| PMA Reference Guide                   | Available on Website                                 |
| Prouduct Overview-PMAFIX Connectors   | Available on Website                                 |
| PMAFIX Connectors-Safety and Sealing  | Available on Website                                 |
| Systems                               |  |
| Certifications                        |  |
| RoHS Compliance                       | Yes  |
|                                       |  |



For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com