

Flexible Conduits & Fittings T&B Catalog Number:

BVYR-362929 78620995425

Status: Active

Description:

UPC Number:

PMAFIX black one-piece 'Y' connector, material - polyamide 6. Fits to conduit size NW -36, 29, 29 . **Application**

Application	
	In a wide range of applications where it is important that the cable protection system offers a high grade
Characteristics	of sealing and safety.
Ondi acteristics	
	Self-extinguishing, free of halogen and cadmium and are extremely shock resistant
	Very high impact resistance
	Vibration-proof connection to PMAFLEX conduits
	Easy mounting, simple conduit push-in instructions
	High conduit pull-out strength
	Can be easily re-opened with a screwdriver
	Very good chemical properties
	Fits both conduit profiles - Fine (T) and coarse (G)
General	
Material	Polyamide 6
Color	Black
Suitable for Use With	PMAFLEX, PMA Smart Line
Dimension Information	
Fits to Conduit Size (NW)	36
Fits to Conduit Size (metric)	40
Fits to Conduit Size (inches)	1 1/4
Output fits to conduit size NW	29
Output fits to conduit size - Metric	32
Technical Information	
Temperature Range-Continuous (Celsius) -40 degree C to +105 degree C
Temperature-Short-Term (Celsius)	+160 degree C
Technical Data Sheet	Available on Website
Chemical Resistance Chart	Available on Website
Specifications	
3dmodel	Available on Website
IP Ratings	
IP Rating	IP68 stat./ IP67 dyn.
Packaging	
T&B Inner Pack	5
Package in Units	50
T&B Sold in UOM	Each
T&B Weight Per UOM	0.25 lbs. Each
Application Support	
PMA Reference Guide	Available on Website
Prouduct Overview-PMAFIX Connectors	Available on Website
	Available on Website



PMAFIX Connectors-Safety and Sealing Systems

Certifications

RoHS Compliance Yes

Certifications



For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321

Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com