



Flexible Conduits & Fittings

T&B Catalog Number:

CYLG-36B.30

UPC Number:

78620995463

Status:

Active

Description:

Coarse profile medium wall very flexible black conduit. (CYL) Material - polyamide 6, conduit size NW - 36.

Application

Machine

Installation Industries

Characteristics

Very good flexibility

Good impact strength, also at low temperatures and dry conditions

Self-extinguishing, free from halogens and cadmium

General

Material	Polyamide 6
Material-Conduit Core	Non-Metallic
Color	Black
System	PMAFLEX
Compatible With	PMAFIX Pro, PMAFIX, PMA Smart Line, PMAGRIP

Dimension Information

Conduit Size (inches)	1 1/4
Conduit Size NW (mm)	36
Conduit Size Metric (mm)	40
Outside Diameter (inches)	1.67
Inside Diameter (mm)	36
Outside Diameter (mm)	42.5
Static Radius (mm)	60
Rec. Fitting Thread-Metric	M40 x 1.5
Rec. Fitting Thread-PG	36

Technical Information

Temperature Range-Continuous (Celsius) -40 to +105

Temperature-Short-Term (Celsius) 160

Fatigue Life High

Technical Data Sheet Available on Website

Chemical Resistance Chart Available on Website

Packaging

T&B Order Multiple	1
T&B Inner Pack	1
Package in Units	6
T&B Sold in UOM	Each
T&B Weight Per UOM	11.4 lbs. Each

Application Support

PMA Reference Guide	Available on Website
PMA Conduit Guide	Available on Website
Product Overview-PMAFLEX Conduits	Available on Website

Certifications

RoHS Compliance

Yes

Certifications



For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com