



## Ferrule

### T&B Catalog Number:

F2051

### UPC Number:

78621033555

### Status:


Active

### Description:

Polypropylene-Insulated Ferrule, Total Length 1.260 Inches/32mm, Pin Length .708 Inches/18mm, Pin Diameter .335 Inches/8.5mm, Base Diameter .492 Inches/12.5mm, Wire Range 2 AWG/35.00mm<sup>2</sup>, Color Red, Copper, Tin Plated

### Features

Ferrules ensure reliable electrical connections when terminating conductors in screw clamp terminal blocks.



### General

|                              |                     |
|------------------------------|---------------------|
| Ferrule Type                 | Insulated           |
| Insulation Type              | Polypropylene       |
| Material                     | Copper              |
| Finish                       | Electro -Tin Plated |
| Color                        | Red                 |
| Wire Range                   | 2                   |
| Wire Size (mm <sup>2</sup> ) | 35.00               |

### Dimension Information

|                     |       |
|---------------------|-------|
| A (mm)              | 32.0  |
| B (mm)              | 18.0  |
| Diameter C (inches) | .335  |
| Diameter C (mm)     | 8.5   |
| Diameter D (inches) | .492  |
| Diameter D (mm)     | 12.5  |
| E (mm)              | .20   |
| A (inches)          | 1.260 |
| B (inches)          | .708  |
| E (inches)          | .008  |

### Specifications

|                     |       |
|---------------------|-------|
| Temperature Rating  | 105°C |
| Flammability Rating | 94HB  |

### Tooling

|                   |                      |
|-------------------|----------------------|
| Tool Charts       | Available on Website |
| Application Tools | ERG4                 |
| Recommended Tool  | ERG4                 |

### Packaging

|                    |                   |
|--------------------|-------------------|
| T&B Order Multiple | 50                |
| T&B Inner Pack     | 50                |
| Package in Units   | 500               |
| T&B Sold in UOM    | Each              |
| T&B Weight Per UOM | 1.19 lbs. per 100 |

### Application Support

|                   |                      |
|-------------------|----------------------|
| Overview          | Available on Website |
| Wire Guide Tables | Available on Website |

### Notes

Ferrule dimensions conform to DIN 46228, Part 4.

### Certifications

|                 |     |
|-----------------|-----|
| RoHS Compliance | Yes |
|-----------------|-----|

### For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)