



RAYVOLVE RVC V-SPLICE MOTOR CONNECTION COVERS

“ROLL-ON” SPLICES FOR 1/C POWER CABLE (1000V)

KEY FEATURES

- Easy connection
- Water resistant seal
- Fast installation
- UL listed and CSA certified

TE Connectivity's (TE) Raychem RVC splice cover kits offer the quick and easy “roll-on” way to insulate and seal stub connections in motors and street lights up to 1000 volts.

The elastomeric RVC cap splice cover provides the required insulation thickness, withstands abrasion, and forms a water-resistant seal. The tool free RVC cap is ideal for installation in cramped motor boxes. It slides on easily and will not leak, unravel, or slip off.

Customers can count on consistent, high quality products, driven by TE's proven innovation and backed by our extraordinary customer support.

**PRODUCT SELECTION INFORMATION: DIMENSIONS IN INCHES (mm)**

Description	Feeder Size (AWG/kcmil)	Bolt Dimension Size (max.)	Bolt Dimension Length (max.)	Lug Length (max.)	Cap Length (max.)	Standard Pack
Motor connections or two-wire stub splices						
RVC-1V	#14 - #4	.375 (8)	.625 (16)	1.75 (45)	3.00 (75)	5
RVC-2V	#8 - 2/0	.375 (8)	.750 (20)	2.75 (70)	4.00 (100)	5
RVC-3V	#2 - 4/0	.500 (12)	1.00 (25)	3.00 (75)	5.25 (130)	5
RVC-4V	250 - 500	.625 (16)	1.50 (35)	5.00 (125)	7.50 (190)	5
	Conductor Size (AWG/kcmil)	Insulation Cut-Back (max.)				
Three-wire stub splices						
RVC-1V	#14 - #8	1.75 (44)				
RVC-2V	#6 - #2	2.75 (70)				

ORDERING INFORMATION

1. Select the appropriate catalog number. Selections are based on typical dimensions of low-voltage insulated cable. Confirm selection with dimensions to assure proper sizing.
2. Kits do not contain connecting lugs or hardware.
3. Each kit contains three Rayvolve RVC splice covers and sealant strips.
4. Standard package: 5 kits/box.

TEST REPORT

Standard test report: EDR-5182
Standard test report: EDR-5183

te.com/energy

©2014 TE Connectivity Ltd. family of companies. All Rights Reserved. E605 11/2014

Rayvolve, Raychem, TE Connectivity and TE connectivity (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE expressly disclaims all implied warranties regarding the information contained herein at any time without notice. TE reserves the right to make any adjustments to the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

FOR MORE INFORMATION: TE Technical Support Centers

USA:	+ 1 800 327 6996
France:	+ 33 380 583 200
UK:	+ 44 0870 870 7500
Germany:	+ 49 896 089 903
Spain:	+ 34 916 630 400
Benelux:	+ 32 16 351 731
Canada:	+ 1 (905) 475-6222
Mexico:	+ 52 (0) 55-1106-0800
Latin/S. America:	+ 54 (0) 11-4733-2200
China:	+ 86 (0) 400-820-6015