

Specification Sheet

Part Number: CTM410C2



KR/CTM series are designed to provide stability to wire bundles.

These mounts can accommodate miniature, intermediate, or standard cross-section cable ties.

Each mount is secured with a single screw.

Cable Tie Anchor Mount, 0.86 x .62", 0.25" Hole Dia, 0.31" Max Tie Width, PA66, White, 100/pkg

|                     |                                                                                                                                                                                                                                                                     |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 151-30703                                                                                                                                                                                                                                                           |
| Type                | CTM4                                                                                                                                                                                                                                                                |
| Color               | White (WH)                                                                                                                                                                                                                                                          |
| Quantity Per        | pack                                                                                                                                                                                                                                                                |
| Product Description | Designed specifically for holding heavier cable bundles these mounting bases can be used in many industries from agriculture to truck manufacture. They offer a very secure fixing and can be used with a wide variety of heavy duty cable ties up to 8.3 mm width. |
| Short Description   | Cable Tie Anchor Mount, 0.86 x .62", 0.25" Hole Dia, 0.31" Max Tie Width, PA66, White, 100/pkg                                                                                                                                                                      |
| Global Part Name    | CTM4-PA66-WH                                                                                                                                                                                                                                                        |

|                                       |                      |
|---------------------------------------|----------------------|
| Length L (Imperial)                   | 0.86                 |
| Length L (Metric)                     | 21.8                 |
| Fixation Method                       | Screw Mount          |
| Width W (Imperial)                    | 0.62                 |
| Width W (Metric)                      | 15.8                 |
| Cable Ties                            | T18 - T120           |
| Height H (Imperial)                   | .37                  |
| Height H (Metric)                     | 9.40                 |
| Cable Tie Width Max (Imperial)        | 0.31                 |
| Cable Tie Width Max (Metric)          | 7.9                  |
| Mounting Hole Diameter D (Imperial)   | 0.25 "               |
| Mounting Hole Diameter D (Metric)     | 6.4 mm               |
| Mounting Hole Diameter D Max (Metric) | 6.4                  |
| Material                              | Polyamide 6.6 (PA66) |
| Material Shortcut                     | PA66                 |

|                               |                                                        |
|-------------------------------|--------------------------------------------------------|
| Flammability                  | UL 94 V-2                                              |
| UV Resistant (Yes/No)         | No                                                     |
| Use Conditions                | For Indoor Use Only                                    |
| Operating Temperature         | -40°F to +185°F (-40°C to +85°C)                       |
| Reach Compliant (Article 33)  | Yes                                                    |
| ROHS Compliant                | Yes                                                    |
| Certification/Specification   | UL   ANSI/UL 1565 UL   ANSI/UL 62275 UL   ANSI/UL 746B |
| UL Recognized (US)            | Yes                                                    |
| UL Recognized (US and Canada) | Yes                                                    |
| Package Quantity (Imperial)   | 100                                                    |
| Package Quantity (Metric)     | 100                                                    |
| Customs Number                | 3926909988                                             |

7930 N. Faulkner Road, Milwaukee, WI 53224  
 Phone: (800) 537-1512 | Email: corp@htamericas.com