

Specification Sheet

Part Number: SM1BK75MT



Fits in holes of all shapes and sizes without the aid of tools or adhesives, making installation easy.

Easily cut to the right length with scissors, thus reducing stock and eliminating waste.

Can be used on any type of material including wood, steel, aluminum, plexiglass and glass, ensuring flexibility of application.

Self-Extinguishing Flexiform Grommet, Panel Thickness 0.039"-0.079", PVC, Black, 75m/roll

|                     |                                                                                                                                                                                              |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 800-00004                                                                                                                                                                                    |
| Type                | SM1                                                                                                                                                                                          |
| Color               | Black (BK)                                                                                                                                                                                   |
| Quantity Per        | pack                                                                                                                                                                                         |
| Product Description | EdgeGuard is used to cover panel edging to protect cables, prevent chafing and provide an attractive finish.The EdgeGuard is manufactured from a flexible PVC compound ensuring ease of use. |
| Short Description   | Self-Extinguishing Flexiform Grommet, Panel Thickness 0.039"-0.079", PVC, Black, 75m/roll                                                                                                    |
| Global Part Name    | SM1-PVC-BK                                                                                                                                                                                   |

Length L (Imperial) 246.1

Length L (Metric) 75

Width W (Imperial) 0.1969

Width W (Metric) 5.0

Height H (Imperial) 0.248

Height H (Metric) 6.3

Panel Thickness Min (Imperial) 0.04

Panel Thickness Max (Imperial) 0.08

Panel Thickness Min (Metric) 1.0

Panel Thickness Max (Metric) 2.0

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability UL 94 HB

Halogen Free No

UV Resistant (Yes/No) No

|                              |                                   |
|------------------------------|-----------------------------------|
| Use Conditions               | For Indoor Use Only               |
| Operating Temperature        | -85°F to +221°F (-65°C to +105°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Package Quantity (Imperial)  | 246                               |
| Package Quantity (Metric)    | 75                                |
| Customs Number               | 3926909988                        |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.  
[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)