

## Specification Sheet

Part Number: TAG10L-105

Laser printable self-laminating polyester has a smooth surface, allowing for the highest resolution and print contrast.

The material is 1.0 mil thick, allowing it to conform around wires and cable.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Lasertags are not affected by the high heat required in a laser printer.



|                |           |
|----------------|-----------|
| Article Number | 594-10105 |
|----------------|-----------|

|      |        |
|------|--------|
| Type | TAG10L |
|------|--------|

|       |            |
|-------|------------|
| Color | White (WH) |
|-------|------------|

|              |      |
|--------------|------|
| Quantity Per | pack |
|--------------|------|

|                     |                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | HellermannTyton's self-laminating labels are used for marking wires and cable. The clear tail overlaps and protects the printed information from abrasion, chemicals and solvents and resists UV exposure. When printed using a laser printer, clear marking and high high-contrast imaging against the wire make this the perfect choice for durable identification. |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                                                                           |
|-------------------|-------------------------------------------------------------------------------------------|
| Short Description | Laser Tag Label, Self-Laminating, 2.0" x .75" x 2.25", 16 Per Sheet, PET, White, 1000/pkg |
|-------------------|-------------------------------------------------------------------------------------------|

|                                 |                                  |
|---------------------------------|----------------------------------|
| Global Part Name                | TAG10L-105-WH                    |
|                                 |                                  |
| Width W (Imperial)              | 2.0                              |
| Width W (Metric)                | 50.8                             |
| Bundle Diameter Min (Imperial)  | 0.25                             |
| Bundle Diameter Min (Metric)    | 6.35                             |
| Bundle Diameter Max (Imperial)  | 0.47                             |
| Bundle Diameter Max (Metric)    | 11.94                            |
| Thickness T (Metric)            | 35.0                             |
| Width of Liner (Metric)         | 215.00                           |
| Width of Liner (Imperial)       | 8.5                              |
| Outside Diameter Max (Imperial) | 0.24                             |
| Outside Diameter Min (Metric)   | 6.1                              |
| Outside Diameter Min (Imperial) | 0.24                             |
| Outside Diameter Max (Metric)   | 12.10                            |
|                                 |                                  |
| Material                        | Type 105, Polyester, white (105) |

|                                |                                   |
|--------------------------------|-----------------------------------|
| Material Shortcut              | 105                               |
| Adhesive                       | Acrylic                           |
| Halogen Free                   | No                                |
| UV Resistant (Yes/No)          | No                                |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature          | -40°F to +300°F (-40°C to +149°C) |
| Reach Compliant (Article 33)   | Yes                               |
| ROHS Compliant                 | Yes                               |
| Package Quantity (Imperial)    | 1000                              |
| Package Quantity (Metric)      | 1000                              |
| Customs Number                 | 3919905060                        |
| Labels per Column              | 4                                 |
| Labels per Row                 | 4                                 |

7930 N. Faulkner Road, Milwaukee, WI 53224  
 Phone: (800) 537-1512 | Email: corp@htamericas.com