


Data Sheet | Item Number: 210-196
Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored
<https://www.wago.com/210-196>



Color:  silver-colored



Dimensions in mm

Technical data	
Main product function	Mounting accessories

Physical data	
Width	2000 mm / 78.74 inches
Height	8.2 mm / 0.323 inches
Depth	35 mm / 1.378 inches

Material Data	
Color	silver-colored
Fire load	0 MJ
Weight	385 g

Commercial data	
Product Group	2 (Terminal Block Accessories)
eCl@ss 10.0	27-40-06-02
eCl@ss 9.0	27-40-06-02
ETIM 8.0	EC001285
ETIM 7.0	EC001285
PU (SPU)	20 (1) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332272315
Customs tariff number	76042990900



Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 210-196

↓

Documentation

Bid Text

210-196	19.02.2019	xml 2.65 KB	↓
210-196	31.08.2017	doc 24.00 KB	↓

CAD/CAE-Data

CAD data

2D/3D Models 210-196

↓

CAE data

EPLAN Data Portal 210-196

↓

WSCAD Universe 210-196

↓

ZUKEN Portal 210-196

↓

1 Compatible Products

1.1 Optional Accessories

1.1.1 Installation

1.1.1.1 Mounting accessories



Item No.: 209-137
Mounting adapter; can be used as end stop; 6.5 mm wide; gray



Item No.: 249-117
Screwless end stop; 10 mm wide; for DIN-rail 35 x 15 and 35 x 7.5; gray



Item No.: 249-197
Screwless end stop; 14 mm wide; for DIN-rail 35 x 15 and 35 x 7.5; gray



Item No.: 249-116
Screwless end stop; 6 mm wide; for DIN-rail 35 x 15 and 35 x 7.5; gray

1.1.2 Marking



1.1.2.1 Label



Item No.: 210-808
Labels; for Smart Printer; 9.5 x 25 mm;
white



Item No.: 210-708
Labels; for TP printers; 9.5 x 25 mm; white

Installation Notes

DIN-Rail	Item No.	Cu rail (A)	Acc. to EN 60947-1
DIN 35 x 7.5 (steel)			
slotted	210-112	76	16A6
unslotted	210-113	76	16A6
DIN 35 x 15 (steel)			
1.6 mm thick	210-114	126	30A2
2.3 mm thick	210-115	126	30A2
DIN 35 x 7.5 (Al)			
unslotted	210-196	76	16A6
DIN 35 x 15 (Al)			
2.3 mm thick	210-198	308	160A40
Current applies to rails of 1 m/33" length			

When using standard DIN-rails as ground conductor busbars, please refer to the maximum current capacities listed above. Steel DIN-rails are not suited for PEN (ground and N-conductor) applications per EN 60947-7-2 (VDE 0611, Part 3).