





Notes

Note	Max. admissible current per the manufacturer's data sheet. With all diodes loaded, the continuous current must be reduced to 0.45 A.
------	--

Electrical data

Operating voltage	≤ AC/DC 250 V
Peak reverse voltage	1000 V
Forward voltage per diode	1.1 V
Forward current per diode (resistive)	1 A
Leakage current	50 µA

Safety and protection

Pollution degree	2
Protection type	IP00; Notice! Live parts can be easily touched! Protection against direct contact must be provided by the equipment manufacturer, e.g., using a WAGO 709 Series Cover (see "Accessories") or a similar cover. The installation guidelines must be observed for each individual application.

Connection data

Connection technology	CAGE CLAMP®
WAGO connector	WAGO 236 Series
Solid conductor	0.08 ... 2.5 mm² / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 2.5 mm² / 28 ... 12 AWG
Strip length	5 ... 6 mm / 0.2 ... 0.24 inches
Note (conductor cross-section)	12 AWG: THHN, THWN



Physical data		
Width		47 mm / 1.85 inches
Height from upper-edge of DIN-rail		65.5 mm / 2.58 inches
Depth		31.5 mm / 1.24 inches

Mechanical Data		
Mounting type		Mounting on DIN-rail via DIN-rail adapter
Housing design		PCB

Material Data		
Fire load		0 MJ
Weight		25.3 g

Environmental requirements		
Ambient temperature (operation at U _N)		-25 ... +40 °C
Surrounding air temperature (storage)		-40 ... +70 °C
Relative humidity		≤ 85% (non-condensing)
Operating altitude (max.)		2000 m

Standards and specifications		
Standards/specifications		EN 61010-2-201

Commercial data		
Product Group		6 (INTERFACE ELECTRONIC)
eCl@ss 10.0		27-14-11-27
eCl@ss 9.0		27-14-11-49
ETIM 8.0		EC000903
ETIM 7.0		EC000903
PU (SPU)		50 (1) pcs
Packaging type		Box
Country of origin		DE
GTIN		4045454193027
Customs tariff number		85369010000