

Item no.: 734-240

Product description: HEADER STRAIGHT SOLDER PIN, 1X1 MM / 0.039X 0.039 IN
10 POLE PIN SPACING 3.81 MM / 0.15 IN 100%
PROTECTED AGAINST MISMATING WITH CLOSED END
MATING DIRECTION PERPENDICULAR TO PCB



Produkt kann von Bild abweichen / product may differ

Packing unit 100 pieces

RoHS compliant

Product group	3 (Multi Conn. System)
Weight	2.59 g
Color	orange
pole count	10
Height	10.3 mm
Height	0.406 in
Width	40.19 mm
Width	1.582 in
Depth	8.5 mm
Depth	0.335 in
Pin spacing from	3.81 mm
Pin spacing from	0.15 in
Pollution degree	2
Measured voltage EN	160 V
Measured shock voltage	2.5 kV
Current intensity EN	10 A
Pollution degree	2

Measured voltage EN	320 V
Measured shock voltage	2.5 kV
Current intensity EN	10 A
Material group	I
Contact material	Electrolytic copper (Ecu)
Contact surface	tin-plated



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
734-240	ABS	04-HG469925/1-PDA	250	10	0,5-1,5
734-240	BV	11915/A0	250	10	0,5-1,5
734-240	CCA	NL5641	250	10	0,5-1,5
734-240	CSA	154112-1465035	300	10	28-14
734-240	DNV	E-9218	250	10	0,5-1,5
734-240	GL	17296-00HH	250	10	0,5-1,5
734-240	KEMA	2077592.02	250	10	0,5-1,5
734-240	LR	96/20035	250	10	0,5-1,5
734-240	RMR	11130002	250	10	0,5-1,5
734-240	UR	E45171	250	10	28-14
734-240	UR	E45172	300	10	

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected