

**GWDR PG21-NP****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Similar to illustration**

In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

**General ordering data**

|            |                                                                 |
|------------|-----------------------------------------------------------------|
| Version    | GWDR NP (flat gasket - neoprene), Sealing ring, PG 21, Neoprene |
| Order No.  | <a href="#">1719590000</a>                                      |
| Type       | GWDR PG21-NP                                                    |
| GTIN (EAN) | 4008190352851                                                   |
| Qty.       | 100 pc(s).                                                      |

**GWDR PG21-NP****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |        |
|------------|--------|
| Net weight | 0.98 g |
|------------|--------|

**Temperatures**

|                             |                  |                             |        |
|-----------------------------|------------------|-----------------------------|--------|
| Operating temperature       | -40 °C... 100 °C | Operating temperature, min. | -40 °C |
| Operating temperature, max. | 100 °C           |                             |        |

**General information**

|                                   |          |                                   |         |
|-----------------------------------|----------|-----------------------------------|---------|
| Cable glands                      | PG 21    | Diameter of sealing ring          | 35 mm   |
| External thread                   | PG 21    | Inside diameter D2                | 28.3 mm |
| Material                          | Neoprene | Number of wires                   | 1       |
| O.D.                              | 35 mm    | Operating temperature range, max. | 100 °C  |
| Operating temperature range, min. | -40 °C   | Silicone                          | No      |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001181    | ETIM 7.0    | EC001181    |
| ETIM 8.0    | EC001181    | ECLASS 9.0  | 27-43-03-19 |
| ECLASS 9.1  | 27-14-44-90 | ECLASS 10.0 | 27-43-03-19 |
| ECLASS 11.0 | 27-43-03-19 | ECLASS 12.0 | 27-43-03-19 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |                                          |
|------------------|------------------------------------------|
| Engineering Data | <a href="#">CAD data – STEP</a>          |
| Engineering Data | <a href="#">WSCAD</a>                    |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |
| Brochures        |                                          |

## GWDR PG21-NP

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

