

SAIE-M12B-5-2.0V-HW-PG9**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Various build-in connectors are required for the connections on the device side of the sensor/actuator cabling. These are available in the versions M12, M8 and M5.

General ordering data

Type	SAIE-M12B-5-2.0V-HW-PG9
Order No.	1233320000
Version	Built-in plugs, M12, Female socket, straight, PG 9, No. of poles: 5, 2 m
GTIN (EAN)	4050118016765
Qty.	1 pc(s).

SAIE-M12B-5-2.0V-HW-PG9**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	76 g
------------	------

Standards

Connector standard	IEC 61076-2-101	Certificate No. (cURus)	E307231
--------------------	-----------------	-------------------------	---------

General data

Cable gland	PG 9	Cable length	2 m
Coding	A	Conductor O.D.	1.5 - 1.7 mm
Conductor O.D., max.	1.7 mm	Conductor O.D., min.	1.5 mm
Contact surface	Gold-plated	Core cross-section	0.34 mm ²
Housing main material	Brass, nickel-plated	No. of poles	5
Pollution severity	3	Protection degree	IP67, when screwed in
Rated current	4 A	Rated voltage	60 V
Strand / cable length	2 m	Temperature range of housing	-30...+90 °C
Type of connection	Socket	connection thread	M12

Classifications

ETIM 6.0	EC002638	eClass 6.2	27-26-07-02
eClass 9.1	27-44-03-09		

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	FL FIELDWIRING EN
--------------------	-----------------------------------

