

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Product image**







In some applications it makes sense to add a test point or a disconnect element to the feed through terminal for testing and safety purposes. With test disconnect terminals you measure electric circuits in the absence of voltage. While the disconnecting points clearance and creepage distance is not assessed in dimensional terms, the specified rated impulse voltage strength must be proven.

# **General ordering data**

Version	SAK Series, Test-disconnect terminal, Rated cross- section: 10 mm², Screw connection, medium yellow, Rail
Order No.	<u>0324120000</u>
Туре	SAKC 10 2STB
GTIN (EAN)	4008190049959
Oty.	50 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

-			
I)ım	ensions	and	weights
	011010110	uiiu	110191110

Depth	52.5 mm	Depth (inches)	2.067 inch
Height	65 mm	Height (inches)	2.559 inch
Width	12 mm	Width (inches)	0.472 inch
Net weight	46.2 g		

# **Temperatures**

Storage temperature	-25 °C55 °C	Continuous operating temp., min.	-60 °C	
Continuous operating temp max	130 °C			

#### **Material data**

Material	KrG	Colour	medium yellow
UL 94 flammability rating	V-0. 5VA		

# **System specifications**

Version	Screw connection, Spacer, With sockets, One end	End cover plate required	
	without connector		Yes
Number of potentials	1	Number of levels	1
Number of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	No	PE connection	No
Rail	TS 32	N-function	No
PE function	No	PEN function	No

#### **Additional technical data**

Explosion-tested version	No	Installation advice	Rail	
Open sides	right	Type of mounting	Snap-on	

# **CSA** rating data

Certificate No. (CSA)	12400-186	Current size C (CSA)	25 A	
Current size D (CSA)	5 A	Voltage size C (CSA)	600 V	
Voltage size D (CSA)	600 V	Wire cross section max. (CSA)	10 AWG	
Wire cross section min. (CSA)	20 AWG			



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

# **Conductors for clamping (rated connection)**

Blade size	1.0 x 5.5 mm	Clamping range, max.	10 mm²
Clamping range, min.	0.33 mm <sup>2</sup>	Clamping screw	M 4
Connection cross-section, stranded,	0.55 11111	Connection cross-section, stranded, min	
max.	10 mm <sup>2</sup>	Connection cross-section, stranded, min	1.5 mm²
Connection direction	on side	Gauge to IEC 60947-1	B6
Number of connections	2	Stripping length	12 mm
Tightening torque, max.	2.4 Nm	Tightening torque, min.	1.2 Nm
Torque level with DMS electric	2.114111	Type of connection	1.2 14111
screwdriver	4	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Screw connection
Wire connection cross section AWG,		Wire connection cross section AWG,	
max.	AWG 8	min.	AWG 22
Wire connection cross section, finely stranded, max.	10 mm²	Wire connection cross section, finely stranded, min.	0.5 mm <sup>2</sup>
Wire connection cross-section, finely stranded with wire-end ferrules DIN	10 2	Wire connection cross-section, finely stranded with wire-end ferrules DIN	0.5
46228/1, max.	10 mm <sup>2</sup>	46228/1, min.	0.5 mm <sup>2</sup>
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	10 mm²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	10 mm²
Wire connection cross-section, solid	10 111111	Wire connection cross-section, solid	10 111111
core, max.	16 mm <sup>2</sup>	core, min.	0.5 mm <sup>2</sup>
Disconnect terminals			
Cross-disconnect	without	Integral test socket	Yes
Slitting	pluggable		
General			
		D-:I	TO 00
Installation advice	Rail	Rail	TS 32
Installation advice Standards	Rail IEC 60947-7-1	Wire connection cross section AWG, max.	AWG 8
		Wire connection cross section AWG,	
Standards Wire connection cross section AWG,	IEC 60947-7-1	Wire connection cross section AWG,	
Standards Wire connection cross section AWG, min.  Rating data	IEC 60947-7-1 AWG 22	Wire connection cross section AWG, max.	AWG 8
Standards Wire connection cross section AWG, min.  Rating data  Rated cross-section	IEC 60947-7-1 AWG 22 10 mm <sup>2</sup>	Wire connection cross section AWG, max.  Rated voltage	AWG 8
Standards Wire connection cross section AWG, min.  Rating data  Rated cross-section  Rated DC voltage	IEC 60947-7-1 AWG 22  10 mm <sup>2</sup> 500 V	Wire connection cross section AWG, max.  Rated voltage Rated current	AWG 8  500 V 26 A
Standards  Wire connection cross section AWG, min.  Rating data  Rated cross-section Rated DC voltage Current at maximum wires  Volume resistance according to IEC	IEC 60947-7-1 AWG 22 10 mm <sup>2</sup>	Wire connection cross section AWG, max.  Rated voltage	500 V 26 A IEC 60947-7-1
Standards  Wire connection cross section AWG, min.  Rating data  Rated cross-section Rated DC voltage Current at maximum wires	10 mm <sup>2</sup> 500 V 27 A	Rated voltage Rated current Standards	AWG 8  500 V 26 A
Standards  Wire connection cross section AWG, min.  Rating data  Rated cross-section Rated DC voltage Current at maximum wires  Volume resistance according to IEC 60947-7-x  Power loss in accordance with IEC	IEC 60947-7-1 AWG 22  10 mm <sup>2</sup> 500 V 27 A 0.56 mΩ	Rated voltage Rated current Standards Rated impulse withstand voltage	500 V 26 A IEC 60947-7-1
Standards  Wire connection cross section AWG, min.  Rating data  Rated cross-section Rated DC voltage Current at maximum wires  Volume resistance according to IEC 60947-7-x  Power loss in accordance with IEC 60947-7-x	IEC 60947-7-1 AWG 22  10 mm <sup>2</sup> 500 V 27 A 0.56 mΩ	Rated voltage Rated current Standards Rated impulse withstand voltage	500 V 26 A IEC 60947-7-1
Standards  Wire connection cross section AWG, min.  Rating data  Rated cross-section Rated DC voltage Current at maximum wires  Volume resistance according to IEC 60947-7-x  Power loss in accordance with IEC 60947-7-x	IEC 60947-7-1 AWG 22  10 mm <sup>2</sup> 500 V 27 A 0.56 mΩ	Rated voltage Rated current Standards Rated impulse withstand voltage	500 V 26 A IEC 60947-7-1 6 kV
Standards  Wire connection cross section AWG, min.  Rating data  Rated cross-section Rated DC voltage Current at maximum wires  Volume resistance according to IEC 60947-7-x  Power loss in accordance with IEC 60947-7-x  UL rating data	IEC 60947-7-1 AWG 22  10 mm <sup>2</sup> 500 V 27 A 0.56 mΩ 1.82 W	Rated voltage Rated current Standards Rated impulse withstand voltage Pollution severity	500 V 26 A IEC 60947-7-1 6 kV
Standards  Wire connection cross section AWG, min.  Rating data  Rated cross-section Rated DC voltage Current at maximum wires  Volume resistance according to IEC 60947-7-x  Power loss in accordance with IEC 60947-7-x  UL rating data  Certificate No. (UR)	IEC 60947-7-1 AWG 22  10 mm <sup>2</sup> 500 V 27 A 0.56 mΩ 1.82 W	Rated voltage Rated current Standards Rated impulse withstand voltage Pollution severity  Conductor size Factory wiring max. (UR)	500 V 26 A IEC 60947-7-1 6 kV 3



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

#### **Classifications**

ETIM 6.0	EC000902	ETIM 7.0	EC000902
ETIM 8.0	EC000902	ETIM 9.0	EC000902
ECLASS 9.0	27-14-11-26	ECLASS 9.1	27-14-11-26
ECLASS 10.0	27-14-11-26	ECLASS 11.0	27-14-11-26
ECLASS 12.0	27-14-11-26	ECLASS 13.0	27250109

# **Environmental Product Compliance**

REACH SVHC	Lead 7439-92-1
SCIP	999cd67e-471e-4085-8dba-1342fcea86de

### **Approvals**

<b>W</b>

ROHS	Conform	
UL File Number Search	UL Website	
Certificate No. (UR)	E60693	

### **Downloads**

Approval/Certificate/Document of	
Conformity	Declaration of Conformity
Engineering Data	CAD data – STEP
User Documentation	Beipackzettel SAKC SAKA.pdf
	<u>StorageConditionsTerminalBlocks</u>
Catalogues	Catalogues in PDF-format



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

#### **Custom printing**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### **General ordering data**

Type DEK 5/6 MC SDR
Order No. 1609830000
GTIN (EAN) 4008190456603

200 pc(s).

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, To customer specification

# **Custom printing**

Qty.



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### General ordering data

Type DEK 5/5 MC SDR

Order No. 1609810000

GTIN (EAN) 4008190456597

Oty. 200 pc(s).

Version

Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

Weidmueller, To customer specification



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

#### **Blank**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### **General ordering data**

Type DEK 5/8 MC NE WS

Order No. 1856740000

<u>856740000</u>

GTIN (EAN) 4032248400850

Qty. 800 pc(s).

Version

Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

Weidmueller, white

#### **Custom printing**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### General ordering data

GTIN (EAN)

Type DEK 5/8 PLUS MC SDR

160 pc(s).

Order No. <u>1046370000</u>

000407000

4032248782079

Version

Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

Weidmueller, To customer specification



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

Туре	DEK 5/8 MC SDR	Version
Order No.	<u>1856750000</u>	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4032248400867	Weidmueller, To customer specification
Qty.	160 pc(s).	

### **Test plugs**



Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

#### **General ordering data**

Туре	PS 4 F.STB 4	Version
Order No.	0299600000	Accessories, Test plug
GTIN (EAN)	4008190074043	
Qty.	20 pc(s).	

# QL / SAKA



Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

# **General ordering data**

Туре	QL 2 SAKA10	Version
Order No.	0135500000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190099404	poles: 2
Qty.	50 pc(s).	
Туре	QL 3 SAKA10	Version
Order No.	0135600000	SAK Series, Cross-connector, Cross-connector, Number of poles: 3
GTIN (EAN)	4008190032081	
Qty.	50 pc(s).	
Туре	QL 4 SAKA10	Version
Order No.	0135700000	SAK Series, Cross-connector, Cross-connector, Number of poles: 4
GTIN (EAN)	4008190118822	
Qty.	50 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

Type QL 10 SAKA10
Order No. 0338500000
GTIN (EAN) 4008190063313
Qty. 20 pc(s).

Version

SAK Series, Cross-connector, for cross-connection link, Number of

poles: 10

#### **Connection sleeves**



#### **General ordering data**

Type VH 13.6/6.3/4.3
Order No. 0299700000
GTIN (EAN) 4008190018313
Oty. 50 pc(s).

Version

SAK Series, Connecting sleeve, for cross-connection link, Number of

poles:

# Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

# **General ordering data**

Type DEK 5/8 PLUS MC NE WS
Order No. 1046350000
GTIN (EAN) 4032248782055
Oty. 800 pc(s).

Version

Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

Weidmueller, white



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

#### **TS 32**

TS 32

Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

# **General ordering data**

Туре	WEW 32/1	Version
Order No.	1067600000	W-Series, End bracket
GTIN (EAN)	4008190099657	
Qty.	50 pc(s).	
Туре	EWK 2	Version
Order No.	0199360000	Accessories, End bracket
GTIN (EAN)	4008190023546	
Qty.	50 pc(s).	
Туре	EWK 1 ALT	Version
Type Order No.	EWK 1 ALT 0495160000	Version Accessories, End bracket
Order No.	0495160000	
Order No. GTIN (EAN)	0495160000 4008190160777	
Order No. GTIN (EAN) Oty.	0495160000 4008190160777 50 pc(s).	Accessories, End bracket
Order No. GTIN (EAN) Oty. Type	0495160000 4008190160777 50 pc(s).	Accessories, End bracket  Version

### Marker holder



The marker holder offer the possibility of additional mounting of standard markers with a pitch of 5 or 5.1 mm. The angled holders can be optionally snaped together and could be mounted in all standard marking channels of the Klippon<sup>®</sup> Connect modular terminal blocks. Fitting marker types could be found under the respective accessories of the designation marking holder.

# **General ordering data**

Туре	BZT 1 WS 10/5	Version
Order No.	1805490000	Accessories, Marker holder
GTIN (EAN)	4032248270231	
Qty.	100 pc(s).	
Туре	BZT 1 ZA WS 10/5	Version
Type Order No.	BZT 1 ZA WS 10/5 1805520000	Version Accessories, Marker holder
	,	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

#### Miscellaneous



We offer a broad portfolio of mounting support for easy handling and supplementation of our products. From various tools to insulating sleeves and various screws, our components are matched to each other down to the last detail and thus facilitate assembly in compliance with the respective standards and protective regulations.

#### **General ordering data**

Type SS M4 D 128-A 4
Order No. 0136400000
GTIN (EAN) 4008190118143
Oty. 100 pc(s).

Version

Accessories, Lock washer

#### **Blank**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### **General ordering data**

Type DEK 5/6.5 MC NE WS Version
Order No. 1609840000 Dekafix,

1609840000 Dekafix, Terminal marker, 5 x 6.5 mm, Pitch in mm (P): 6.50

GTIN (EAN) 4008190203429 Weidmueller, white

Qty. 900 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

#### **SAK-Series**

SAK Series End plates are fitted to the open side of the last modular terminal before the end bracket. The use of an end plate ensures the function of the modular terminal and the specified rated voltage. It guarantees protection against contact with live parts and makes the final terminal finger-proof.

#### **General ordering data**

Туре AP SAKB/C/T KRG Order No. 0146720000 GTIN (EAN)

4008190027995

Qty. 20 pc(s).

SAK Series, End plate, 3 mm, dark beige, yellow, Direct mounting

#### **SAK-Series**



Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

#### General ordering data

Туре FW 35 Order No. 0383560000 GTIN (EAN) 4008190181314 Qty.

50 pc(s).

Version

Accessories, End bracket



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# Accessories

# **End plate**



### **Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

### **General ordering data**

Type TW SAKB/C/T
Order No. 0242920000
GTIN (EAN) 4008190069933
Oty. 20 pc(s).

Version

SAK Series, Partition plate, 3 mm, beige, Direct mounting

#### **Screws**



Depending on the terminal block or also accessories, we offer different types of screws as additional items or also spare parts.

#### **General ordering data**

Type BFSC M4X20
Order No. 0362800000
GTIN (EAN) 4008190114053
Oty. 100 pc(s).

Version

Accessories, Mounting screw, for cross-connection link



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# Accessories

#### **Blank**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### **General ordering data**

Type DEK 5/6 MC NE WS
Order No. 1609820000
GTIN (EAN) 4008190203436
Qty. 1,000 pc(s).

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, white



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# Accessories

#### **DEK 5/6**



#### WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

#### Your benefits with MultiMark

- · Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

# **General ordering data**

Type DEK 5/6 MM WS
Order No. 2007120000
GTIN (EAN) 4050118392104
Oty. 600 pc(s).

Version

Dekafix, Terminal marker, 5 x 6 mm, Weidmueller, white

#### W-Series



A partition plate is used for the optical separation of circuits or used for electrical isolation from neighbouring cross-connectors. In contrast to the end plate, the contour can be larger than the adjacent terminal blocks. However, it should not be smaller, as otherwise the required clearance and creepage distances within the application can no longer be maintained.

#### General ordering data

Type WTW EN

Order No. 1058800000

GTIN (EAN) 4008190140175

Oty. 20 pc(s).

Version

W-Series, Partition plate



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# Accessories

#### **DEK 5/8**



# WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

### Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

# **General ordering data**

Туре	DEK 5/8 MM WS	Version
Order No.	<u>2007130000</u>	Dekafix, Terminal marker, 5 x 8 mm, Weidmueller, white
GTIN (EAN)	4050118392012	
Qty.	500 pc(s).	



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

#### **Custom printing**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### **General ordering data**

Type DEK 5/6.5 MC SDR
Order No. 1609850000
GTIN (EAN) 4008190456610
Oty. 180 pc(s).

Version

Dekafix, Terminal marker, 5 x 6.5 mm, Pitch in mm (P): 6.50

Weidmueller, To customer specification

### Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### General ordering data

Type DEK 5/5 MC NE WS

Order No. 1609801044

GTIN (EAN) 4008190397111

Oty. 1,000 pc(s).

Version

Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

Weidmueller, white