

**Connecting elements**  
**H1,0/12 GE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



- supplied loose in polybag
- Weidmüller colour code
- DIN colour code

**General ordering data**

|            |                                                 |
|------------|-------------------------------------------------|
| Type       | H1,0/12 GE                                      |
| Order No.  | <a href="#">0409700000</a>                      |
| Version    | Wire end ferrule, insulated, 8 mm, 6 mm, Yellow |
| GTIN (EAN) | 4008190152222                                   |
| Qty.       | 500 pc(s).                                      |
| Packaging  | loose                                           |

## Connecting elements

### H1,0/12 GE

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Dimensions and weights

|            |        |                |            |
|------------|--------|----------------|------------|
| Width      | 12 mm  | Width (inches) | 0.472 inch |
| Net weight | 0.08 g |                |            |

### Technical data

|         |           |
|---------|-----------|
| Version | insulated |
|---------|-----------|

### Wire-end ferrules

|                                         |                   |                               |             |
|-----------------------------------------|-------------------|-------------------------------|-------------|
| Collar diameter (D2)                    | 3 mm              | Colour code                   | Weidmüller  |
| Conductor cross-section                 | 1 mm <sup>2</sup> | Contact surface diameter (D1) | 1.4 mm      |
| Contact surface length (L2)             | 6 mm              | L1 in mm                      | 12 mm       |
| Metal sleeve thickness (S1)             | 0.15 mm           | Military designation          | T 20A 004 A |
| Plastic collar thickness (S2)           | 0.25 mm           | Stripping length              | 8 mm        |
| Wire connection cross section AWG, max. | AWG 17            |                               |             |

### Classifications

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000005    | ETIM 4.0   | EC000005    |
| ETIM 5.0   | EC000005    | ETIM 6.0   | EC000005    |
| UNSPSC     | 31-16-31-02 | eClass 5.1 | 27-40-02-01 |
| eClass 6.2 | 27-40-02-01 | eClass 7.1 | 27-40-02-01 |
| eClass 8.1 | 27-40-02-01 | eClass 9.0 | 27-40-02-01 |
| eClass 9.1 | 27-40-02-01 |            |             |

### Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |                                          |
|--------------------|------------------------------------------|
| Brochure/Catalogue | <a href="#">CAT 6 TOOLS 15/16 EN</a>     |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a> |

### Connecting elements H1,0/12 GE

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Similar to illustration

---

