

Accessories
TS 32X15/LL 2M/ST/ZN**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Product image

Similar to illustration

General ordering data

Type	TS 32X15/LL 2M/ST/ZN
Order No.	0514400000
Version	Rail, TS 32, with slot, Steel, galvanic zinc plated and passivated
GTIN (EAN)	4008190086152
Qty.	2 m

Accessories

TS 32X15/LL 2M/ST/ZN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Width	32 mm	Width (inches)	1.26 inch
Height	33 mm	Height (inches)	1.299 inch
Depth	15 mm	Depth (inches)	0.591 inch
Net weight	667 g		

Mounting rail

Drill-hole diameter	5.2 mm	Short circuit strength corresponds to E-Cu wire	35 mm ²
Short-time withstand current according to IEC 60947-7-2	4.2 kA/1s	Slit gap	11 mm
Slit length	25 mm	Slit width	5.2 mm
Slotted drill holes	Yes	Solder eyelet hole diameter (D)	5.2 mm
Spacing of holes, centre-to-centre	36 mm	Thickness	1.5 mm

Classifications

ETIM 6.0	EC001285	ETIM 7.0	EC001285
eClass 9.0	27-40-06-02	eClass 9.1	27-40-06-02
eClass 10.0	27-40-06-02	UNSPSC	30-21-18-01

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 1 TERM 16/17 EN
Engineering Data	EPLAN, WSCAD, Zuken E3.S
Engineering Data	STEP
User Documentation	StorageConditionsTerminalBlocks