

Detailed information for: S202-K3

This page contains technical data sheet, documents library and links to offering related to this product. If you require any other information, please contact us using form located at the bottom of the page.

- Data Sheet
- Documentation

S202-K3

General Information

Extended Product Type:S202-K3

Product ID:	2CDS252001R0317
EAN:	4016779507356
Catalog Description:	Miniature Circuit Breaker - S200 - 2P - K

Long Description: System pro M compact S200 miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 6 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs of the product range S200 comply with IEC/EN 60898-1, IEC/EN 60947-2, UL1077 and CSA 22.2 No. 235, allowing the use for residential, commercial and industrial applications. Bottom-fitting auxiliary contact can be mounted on S200 to save 50% space.

Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Miniature Circuit Breakers MCBs



+ Accessories

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362010

Popular Downloads

Data Sheet, Technical Information: [2CDC002157D0102](#)

Dimensions

Product Net Width:	35 mm
Product Net Depth:	69 mm

Product Net Height:	88 mm
Product Net Weight:	0.25 kg

Technical

Standards:	IEC/EN 60947-2 UL 1077
------------	---------------------------

Number of Poles:	2
------------------	---

Tripping Characteristic:	K
--------------------------	---

Rated Current (I _n):	3 A
----------------------------------	-----

Rated Operational Voltage:	acc. to IEC 60898-1 400 V AC acc. to IEC 60947-2 440 V AC
----------------------------	--

Power Loss:	2.4 W at Rated Operating Conditions per Pole 1.2 W
-------------	---

Rated Insulation Voltage (U _i):	acc. to IEC/EN 60664-1 440 V
---	------------------------------

Operational Voltage:	Maximum (Incl. Tolerance) 125 V DC Maximum (Incl. Tolerance) 440 V AC Minimum 12 V AC / 12 V DC
----------------------	---

Rated Frequency (f):	50 Hz 60 Hz
----------------------	----------------

Rated Ultimate Short-Circuit Breaking Capacity (I _{cU}):	(230 V AC) 20 kA (440 V AC) 10 kA
--	--------------------------------------

Rated Service Short-Circuit Breaking Capacity (I _{cS}):	(230 V AC) 15 kA
---	------------------

Energy Limiting Class:	3
------------------------	---

Overvoltage Category:	III
-----------------------	-----

Pollution Degree:	3
-------------------	---

Rated Impulse Withstand Voltage (U _{imp}):	4 kV (6.2 kV @ sea level) kV (5.0 kV @ 2000 m) kV
--	---

Dielectric Test Voltage:	50 / 60 Hz, 1 min: 2 kV
--------------------------	-------------------------

Housing Material:	Insulation Group II, RAL 7035
-------------------	-------------------------------

Actuator Type:	Insulation group II, black, sealable
----------------	--------------------------------------

Contact Position Indication:	Red ON / Green OFF
------------------------------	--------------------

Degree of Protection:	IP20
-----------------------	------

Remarks:	IP40 in enclosure with cover
----------	------------------------------

Electrical Endurance:	20000 AC cycle
-----------------------	----------------

Mechanical Endurance:	20000 cycle
-----------------------	-------------

Terminal Type:	Screw Terminals
----------------	-----------------

Screw Terminal Type:	Failsafe Bi-directional Cylinder-lift Terminal
----------------------	--

Connecting Capacity:	Busbar 10 / 10 mm ² Flexible with Ferrule 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Rigid 0.75 ... 35 mm ² Stranded 0.75 ... 35 mm ²
----------------------	--

Tightening Torque:	2.8 N·m
--------------------	---------

Recommended Screw Driver:	Pozidriv 2
---------------------------	------------

Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
-----------------------	--

Mounting Position:	Any
--------------------	-----

Environmental

Ambient Air Temperature:	Operation -25 ... +55 °C Storage -40 ... +70 °C
Resistance to Shock acc. to IEC 60068-2-27:	25g / 2 shocks / 13 ms
Resistance to Vibrations acc. to IEC 60068-2-6:	5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In
Environmental Conditions:	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	110 V DC 480Y / 277 V AC
Connecting Capacity UL/CSA:	Busbar 18-8 AWG Conductor 18-4 AWG
Tightening Torque UL/CSA:	25 in·lb
Interrupting Rating acc. to UL1077:	(110 V DC) 10 kA (277 V AC) 6 kA (480Y / 277 V AC) 6 kA

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CDK403001D0604
Environmental Information:	2CDK400030D0201
Instructions and Manuals:	2CSC400002D0208
RoHS Information:	2CDK400003K0201

Container Information

Package Level 1 Units:	5 piece
Package Level 1 Width:	92 mm
Package Level 1 Length:	183 mm
Package Level 1 Height:	80 mm
Package Level 1 Gross Weight:	1.3 kg
Package Level 1 EAN:	4016779608565
Package Level 2 Units:	60 piece
Package Level 2 Width:	275 mm
Package Level 2 Length:	395 mm
Package Level 2 Height:	210 mm
Package Level 2 Gross Weight:	14.8 kg
Package Level 2 EAN:	4016779972499

Classifications

Object Classification Code:	F
E-nummer:	2100709
ETIM 4:	EC000042 - Miniature circuit breaker (MCB)
ETIM 5:	EC000042 - Miniature circuit breaker (MCB)
ETIM 6:	EC000042 - Miniature circuit breaker (MCB)

Contact information

What would you like to do?

I need more information

ABB Sales

Submit your inquiry

Country

United States of America ▼

Name

Company

E-Mail

Phone

Zip code

Your message

→ [Privacy policy](#)

[Cancel](#)

[Send message](#)

Your local ABB Sales Team

Name

Customer Support

▲ [Close](#)