

Detailed information for: K6-22Z-84

This page contains technical data sheet, documents library and links to offering related to this product. If you require any other information, please contact us using form located at the bottom of the page.

[Print...](#)
[Print to Pdf...](#)

Data Sheet

Documentation

K6-22Z-84

General Information

Extended Product Type:K6-22Z-84

Product ID: GJH1211001R8224

EAN: 4013614151309

Catalog Description: K6-22Z-84 Mini Contactor Relay

Long Description: The K6-22Z mini contactor relay is a compact 4 pole contactor relay with screw terminals. They are ideally suited for applications where reliability is a must and space is at a premium. Mini contactors relays are used in residential buildings, commercial buildings and industrial applications for switching of control signals up to 3 A / 400 V (AC-15). Further features are the silent coil, a switch position indication and the integrated possibility for rail or wall mounting.

Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Mini Contactors



Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85365080

Popular Downloads

Data Sheet, Technical Information: [1SBC100173C0201](#)

Dimension Diagram: [GJL1200436F0001](#)

Dimensions

Product Net Width: 52.5 mm

Product Net Height: 57.5 mm

Product Net Depth:	46.5 mm
Product Net Weight:	0.175 kg

Technical

Number of Poles:	4
------------------	---

Mini Contactor Type:	Mini Contactor Relay
----------------------	----------------------

Rated Operational Voltage:	Auxiliary Circuit 12 ... 240 V DC Auxiliary Circuit 12 ... 500 V AC/DC Auxiliary Circuit 690 V
----------------------------	--

Rated Frequency (f):	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Control Circuit 400 Hz Control Circuit 50 Hz Control Circuit 60 Hz Main Circuit 60 Hz Main Circuit 50 Hz Main Circuit DC
----------------------	---

Rated Impulse Withstand Voltage (U _{imp}):	Auxiliary Circuit 6 kV
--	------------------------

Rated Insulation Voltage (U _i):	690 V acc. to UL/CSA 600 V
---	-------------------------------

Number of Main Contacts NC:	0
-----------------------------	---

Number of Main Contacts NO:	0
-----------------------------	---

Number of Auxiliary Contacts NC:	2
----------------------------------	---

Number of Auxiliary Contacts NO:	2
----------------------------------	---

Rated Operational Current AC-15 (I _e):	(120 V) 4 A (220 / 240 V) 4 A (240 V) 4 A (24 V) 4 A (380 / 400 V) 3 A (500 V) 2 A
--	---

Rated Operational Current DC-13 (I _e):	(110 V) 0.7 A (220 / 240 V) 0.4 A (24 V) 2.5 A
--	--

Conventional Free-air Thermal Current (I _{th}):	Auxiliary Circuit 6 A
---	-----------------------

Rated Control Circuit Voltage (U _c):	110 ... 127 V AC
--	------------------

Coil Operating Limits:	(acc. to IEC 60947-5-1) for AC supply 0.85 ... 1.1 x U _c (at $\theta \leq 55\text{ }^{\circ}\text{C}$)
------------------------	--

Degree of Protection:	Auxiliary Circuit Terminals IP20 Control Circuit Terminals IP20
-----------------------	--

Mechanical Durability:	10000000 cycle
------------------------	----------------

Minimum Switching Capacity:	17 V 5 mA
-----------------------------	--------------

Maximum Electrical Switching Frequency:	AC-15 600 cycles per hour DC-13 600 cycles per hour
---	--

Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 1/2x 1 ... 2.5 mm ² Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 1 ... 4 mm ²
--	---

Connecting Capacity Control Circuit:	Flexible with Ferrule 1/2x 1 ... 2.5 mm ² Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 1 ... 4 mm ²
--------------------------------------	---

Wire Stripping Length:	Auxiliary Circuit 9 mm
------------------------	------------------------

Tightening Torque:	Auxiliary Circuit 0.8 ... 1.1 N·m Control Circuit 0.8 ... 1.1 N·m
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Power Loss:	at Rated Operating Conditions per Pole 2 W
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1

Environmental

Ambient Air Temperature:	Operation -25 ... +55 °C Storage -40 ... +80 °C
Maximum Operating Altitude Permissible:	2000 m
Resistance to Shock acc. to IEC 60068-2-27:	11 ms Pulse 15g
Resistance to Vibrations acc. to IEC 60068-2-6:	3g / 3 ... 150 Hz
RoHS Status:	Following EU Directive 2011/65/EC

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Auxiliary Circuit 600 V AC/DC
General Use Rating UL/CSA:	(600 V AC) 5 A
Contact Rating UL/CSA:	A600
Connecting Capacity Auxiliary Circuit UL/CSA:	Stranded 1/2x 22-10 AWG
Tightening Torque UL/CSA:	Auxiliary Circuit 7 in·lb Control Circuit 7 in·lb

Certificates and Declarations (Document Number)

CB Certificate:	1SAA938001-2001
CCC Certificate:	1SAA938000-3804
cUL Certificate:	cUL_E48139
Declaration of Conformity - CE:	1SAD938512-0001
EAC Certificate:	1SAA938001-2701
Environmental Information:	1SAA938002-2401
Instructions and Manuals:	2CDC102047M6801
RMRS Certificate:	1SAA938001-0704
RoHS Information:	1SAD938512-0001
UL Certificate:	UL_E48139

Container Information

Package Level 1 Units:	10 piece
Package Level 1 Width:	115 mm
Package Level 1 Height:	54 mm
Package Level 1 Length:	280 mm
Package Level 1 Gross Weight:	1.82 kg

Classifications

Object Classification Code: K

ETIM 4: EC000196 - Contactor relay

ETIM 5: EC000196 - Contactor relay

ETIM 6: EC000196 - Contactor relay

eClass: 7.0 27371001

UNSPSC: 39121500

Contact information

What would you like to do?

I need more information

ABB Sales

Submit your inquiry

Country

United States of America ▼

Name

Company

E-Mail

Phone

Zip code

Your message

→ [Privacy policy](#)

Cancel

Send message

Your local ABB Sales Team

Name

Customer Support

▲ Close