



 Active

RoHS Compliant (Statement of Compliance)

? Header
? Header Type = Breakaway
? Number of Rows = Single
? Number of Positions = 16
? Mating Post Length = 8.00 mm

[View all Features](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

? [AMPMODU II STIFTFLEISTEN, EINREIHIG](#) (PDF, German)

? None Available

? None Available

? None Available

? None Available

? None Available

List all Documents

? Product Line Information

? Tooling

- ? Product Type = Header
- ? Number of Positions = 16
- ? Mount Angle = Vertical
- ? PCB Retention Feature = No
- ? Surface Mount Compatible = No
- ? Board Standoff = Without
- ? Mounting Ears = Without
- ? Mating Connector Lock = Without
- ? Profile = Standard

? Mating Post Length (mm [in]) = 8.00 [0.315]
? Panel Attachment = Without

? Termination Post Length (mm [in]) = 3.20
[0.126]

? Header Type = Breakaway
 ? Number of Rows = Single
 ? Centerline, Matrix (mm [in]) = 2.54 [.100]
 ? Selectively Loaded = No
 ? Mount Type = PC Board

? Contact Mating Area Plating = Gold (30)
 ? High Speed Serial Data Connector = No
 ? Contact Material = Phosphor Bronze
 ? Contact Termination Area Plating = Tin

? Housing Material = Thermoplastic Polyester
 ? Housing Flammability Rating = UL 94V -0

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? High Temperature Housing = No

? Brand = AMP