



+ CONNECTORS

USB



✓ Active

TE CONNECTIVITY (TE)
USB A R/A STAK ASSY THRU HOLE

Universal Serial Bus | A

5787745-5
TE Internal Number: 5787745-5

EU RoHS Compliant
EU ELV Compliant

USB Type A
USB Version 2.0
Size Standard
Connector Style Receptacle
Number of Ports 2

↓ PRODUCT DRAWING
English

↓ 3D PDF

DOCUMENTATION

Product Drawings

RECEPTACLE ASSEMBLY, RIGHT ANGLE, STACKED, THRU-HOLE, USB

PDF
English

CAD Files

3D PDF
PDF
3D

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Product Specifications

Application Specification

Universal Serial Bus (USB) Connectors

PDF

English

Product Specification

Product Specification For Usb Consortium Plug & Receptacle Lead Free Version

PDF

English

Qualification Test Report

Test Report For USB Consortium Plug & Receptacle Lead Free Version

PDF

English

Product Environmental Compliance

TE Material Declaration

USB A R/A STAK ASSY THRU HOLE

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

USB Type A

USB Version 2.0

Size Standard

Connector Style Receptacle

Orientation Right Angle

Connector & Contact Terminates To Printed Circuit Board

LED Without

Product Type Connector

Configuration Features

Number of Ports 2

Number of Positions 8

Panel Ground With

Panel Ground Type Ground Finger

Panel Ground Location Between Ports

Body Features

Shell Plating Finish Bright
Shell Plating Material Tin

Contact Features

Contact Mating Area Plating Thickness .76 µm [29.92 µin]
Contact Mating Area Plating Material Gold or Gold Flash over Palladium Nickel

Termination Features

Termination Method Solder
Contact Termination Type Through Hole

Mechanical Attachment

Locating Posts Without
Mounting Location Top
Locking Feature Without
PCB Mount Retention Type Kinked Legs

Housing Features

Housing Color Black
Housing Material Thermoplastic

Dimensions

PCB Thickness (Recommended) 1.57 mm [.062 in]
Tail Length 2.29 mm [.09 in]

Operation/Application

Pick and Place None

Industry Standards

Industry Standard USB 2.0

Packaging Features

Packaging Method Box & Tray, Tray
Packaging Quantity 88

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance
PDF

