


 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



 Active

 Add to Part List

Always EU RoHS/ELV Compliant (Statement of Compliance)

- ? Receptacle
- ? Tab Fit = 2.79 x 0.51 mm
- ? Wire Range = 0.50 -1.40 ² [20-16] mm [AWG]
- ? Insulation Diameter = 2.00 -3.00 [.079 -.118] mm [in]
- ? Receptacle Style = Straight

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

Product Drawings:

[110" SERIES FASTIN FASTON RECEPTACLE](#) (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

['110' Series FASTIN -FASTON* Connector](#) (PDF, Japanese)

Application Specifications:

? None Available

Instruction Sheets:

? None Available

CAD Files: ([CAD Format & Compression Information](#))

- ? 2D Drawing (DXF, Version N)
- ? 3D Model (IGES, Version N)
- ? 3D Model (STEP, Version N)

Additional Information:

? Product Line Information

Related Products:

? Tooling

List all Documents

Product Features

Product Type Features:

? Product Type = Receptacle
 ? Tab Fit (mm [in]) = 2.79 x 0.51 [.110 x .020]
 ? Insulation Diameter (mm [in]) = 2.00 -3.00
 [.079 -.118]
 ? Receptacle Style = Straight
 ? Wire/Cable Type = Regular Wire
 ? Finish = None
 ? Material = Brass
 ? Insertion Force = Normal
 ? Insulation Support = With
 ? Crimp Type = F -Crimp
 ? FASTON = Yes
 ? For Housing Type = Multiple

Body Related Features:

? Wire Range (mm [AWG]) = 0.50 - 1.40 ² [20-16]
 ? Stock Thickness (mm [in]) = 0.51 [0.020]

Industry Standards:

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Not relevant for lead free process
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

? Packaging Method = Strip

Other:

```
? Line = FASTIN -FASTON .110
? Brand = AMP
```