

 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Product Highlights:

- Receptacle
- Tab Fit = 6.35 x 0.64 mm
- Board Mount = No
- Receptacle Style = Straight
- Insulation Support

TE Part Number: 444335-2

Active

 Add to Part List

Product Drawings:

- [L.I.F. FASTON RECEPT. .250](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- Product Line Information

Related Products:

- Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Receptacle
- Tab Fit (mm [in]) = 6.35 x 0.64 [.250 x .025]
- Receptacle Style = Straight
- Insulation Support = Insulation Support
- Wire/Cable Type = Stranded
- Insulation Diameter (mm [in]) = 3.00-4.29 [.118-.169]
- Insertion Force = Low
- Material = Brass
- Finish = Tin
- Crimp Type = F-Crimp

Mechanical Attachment:

- Board Mount = No

Body Related Features:

- Weld Tab = Without
- Wire Range (mm [AWG]) = 1.00-2.50² [17-13.5]
- Length (mm [in]) = 17.10 [0.673]
- Stock Thickness (mm [in]) = 0.41 [0.016]

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Related Features:

- Packaging Method = Reel

Other:

- For Hermetic Header Tab = No
- Line = FASTON .250
- Brand = AMP