

-1



Active

RoHS Compliant (Statement of Compliance)

- ? Plug
- ? Number of Positions = 36
- ? PCB Mount Style = Right Angle
- ? Standard Orientation
- ? Standard Profile

[View all Features](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

Product Drawings:

? [PLUG ASSEMBLY, 36 POSITION, RIGHT ANGLE, SELF - TAPPIN...](#)
(PDF, English)

? None Available

? None Available

? None Available

? None Available

? None Available

? Product Line Information

? Tooling

List all Documents

(Please use the Product Drawing for all design activity)

- ? Gender = Plug
- ? Number of Positions = 36
- ? PCB Mount Style = Right Angle
- ? Orientation = Standard
- ? Profile = Standard
- ? Shielded = No
- ? Mating Connector Lock = Without
- ? Special PCB Retention = With
- ? Special PCB Retention Method = Self - Tapping
- ? Grounded = No
- ? Panel Thickness (mm [in]) = 1.57 [0.062]
- ? Color = Black
- ? Bracket Material = Thermoplastic

- ? Panel Attachment = With
- ? Panel Attachment Style = Rear Mount
- ? Plate Material = Thermoplastic
- ? Comb Material = Thermoplastic

? Solder Tail Plating = Tin

? PCB Tail Length (mm [in]) = 4.75 [0.187]

? Contact Mating Area Plating = Gold over Nickel

? Contact Material = Copper Alloy

?	Housing Material = Thermoplastic	
?	Housing Flammability Rating = UL 94V	-0

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? Brand = AMP