

Flexible Film Connectors



6 - 176982 - 0

 Active

RoHS Compliant (Statement of Compliance)

- ? Connector
- ? 2.54 mm Centerline
- ? Connector Type = Trio -Mate
- ? Number of Positions = 10
- ? Number of Rows = Single

[View all Features](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

? TRIOMATE HORIZONTAL CABLE ENTRY FOR 1.57 [.062] THK ...
(TIF, English)

? None Available

? None Available

? None Available

? None Available

? None Available

List all Documents

? Product Line Information

? [Leg Style](#)

? [Recommended Mounting Hole Pattern](#)

? Tooling

- ? Product Type = Connector
- ? Connector Type = Trio -Mate
- ? Number of Positions = 10
- ? PCB Thickness (mm [in]) = 1.57 [0.062]
- ? Mating Connector Lock = Without
- ? Mating Polarization = Without
- ? Mounting Ears = Without
- ? Color = Black

? Panel Attachment = Without

? Termination Post Length (mm [in]) = 3.05
[0.120]

? Centerline (mm [in]) = 2.54 [0.100]
 ? Number of Rows = Single
 ? Cable Entry Angle = Right Angle

- ? Contact Mating Area Plating = Pre Tin
- ? Contact Material = Phosphor Bronze

?	Housing Material = Thermoplastic Glass reinforced	
?	Housing Flammability Rating = UL 94V	-0

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? Terminate To = Printed Circuit Board

? Brand = AMP