

 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



 Active

Always EU RoHS/ELV Compliant (Statement of Compliance)

? Receptacle
? Tab Fit = 6.35 x 0.81 mm
? Board Mount = No
? Receptacle Style = Straight
? Insulation Support

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

[RECPT, FASTON, LOW - INSERTION, .250 SERIES](#) (PDF, English)

? None Available

? None Available

[Wire Preparation And Crimp Inspection Guide](#) (PDF, English)

? None Available

? None Available

List all Documents

? Product Line Information

? Tooling

? Product Type = Receptacle
 ? Tab Fit (mm [in]) = 6.35 x 0.81 [.250 x .032]
 ? Receptacle Style = Straight
 ? Insulation Support = Insulation Support
 ? Wire/Cable Type = Regular Wire
 ? Insulation Diameter (mm [in]) = (2) 3.05
 [.120] Max., 5.33 -6.73 [.210 -.265]
 ? Insertion Force = Low
 ? Material = Brass
 ? Finish = Tin
 ? Crimp Type = "F"
 ? CSA Certified = Yes

? Board Mount = No

? Weld Tab = Without

? Wire Range (mm [AWG]) = (2) 0.80 - 0.90 ² [(2) 18], 1.25 - 3.00 ² [16 - 12]

? UL Rating = Listed

? Stock Thickness (mm [in]) = 0.43 [0.017]

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Not relevant for lead free process
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? Packaging Method = Strip

? For Hermetic Header Tab = No

? Line = Budget

? Brand = AMP