



[+ TERMINALS & SPLICES](#)
[QUICK DISCONNECTS](#)



✓ Active

TE CONNECTIVITY (TE)
FASTON 187 FLAG 18-14 AWG TPBR
[FASTON](#) | [187](#)

63652-1
TE Internal Number: 63652-1

[EU RoHS Compliant](#)
[EU ELV Compliant](#)

Terminal Type Tab
Wire Size (AWG) 18 – 14
Mating Tab Width 4.75 mm [.187 in]
Mating Tab Thickness .81 mm [.032 in]
Terminal Orientation Flag

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**

DOCUMENTATION

Product Drawings

TAB, FASTON, FLAG, 4.75 [.187] SERIES
PDF
English

CAD Files

3D PDF
PDF
3D

Customer View Model

2D_DXF.ZIP

English

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

- Terminates To** Wire & Cable
- FASTON** Yes
- Insulated Wire Support** Yes
- Disconnect Type** Quick Connect
- Insertion Force** Low
- Insulated** No
- Wire/Cable Type** Discrete Wire
- Wire Stop** No
- Wire/Cable Composition** Stranded

Configuration Features

- Connection Capacity** Single

Body Features

- Plating Material** Tin

Contact Features

- Terminal Type** Tab
- Terminal Orientation** Flag
- Barrel Type** Open
- Crimp Type** Tab-Lok

Mechanical Attachment

- Mating Retention Type** Dimple

Dimensions

- Wire Size (AWG)** 18 – 14
- Mating Tab Width** 4.75 mm [.187 in]
- Mating Tab Thickness** .81 mm [.032 in]
- Accepts Wire Insulation Diameter Range** 2.03 – 3.05 mm [.08 – .12 in]
- Receptacle Stock Thickness** .81 mm [.032 in]
- Wire Insulation Diameter (Max)** 3.05 mm [.12 in]
- Overall Length** 11.38 mm [.448 in]

Industry Standards

UL Rating Listed

Packaging Features

Packaging Method Reel

Packaging Quantity 4000

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF