

5352115-1 Product Details

Have a Question?

Chat with a Product Information Specialist



5352115-1

TE Internal Number: 5352115-1

Active

2mm Hard Metric PCB Mount Connectors (Z-PACK 2mm HM)

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Connector Assembly
- Connector Style = Receptacle
- Type = Type C
- Interface Type = 2mm HM

[View all Features](#)

- Quick Links
- Check Pricing & Availability
 - Search for Tooling
 - View Mating Products (2)
 - Product Feature Selector
 - Contact Us About This Product

View 3D PDF

Add to My Part List Request Sample Find Similar Products Buy Product

Documentation & Additional Information	
Product Drawings: Z-PACK 2mm HM TYPE C - 11 COLUMNS PRE-SHIELDED RECEP... (PDF, English) Catalog Pages/Data Sheets: - None Available Product Specifications: Z-Pack 2 mm HM CONNECTORS (PDF, English) Application Specifications: Z-PACK 2mm HM Interconnection System for Board-to-Bo... (PDF, English) Instruction Sheets: - None Available CAD Files: (CAD Format & Compression Information) 2D Drawing (DXF, Version G3) 3D Model (IGES, Version G3) 3D Model (STEP, Version G3) List all Documents	Additional Information: Product Line Information Related Products: Tooling Mating Products (2)

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: - Product Type = Connector - Connector Type = Connector Assembly - PCB Mount Angle = Right Angle - Mating Polarization = With - Mating Polarization Type = Multi-Purpose Center - Comment = Female connector with pre-installed shield. Mechanical Attachment: - Board Mount = Free Board - Module Length (mm [in]) = 50.00 [1.968] - Crosstalk Version = Standard - Shield Type = Ground Return Shielding - Shield Style = Upper Electrical Characteristics: - Shielded = Yes Termination Related Features: - Interface Type = 2mm HM - Termination End Plating = Tin over Nickel Body Related Features: - Type = Type C - Number of Rows = 5 - Number of Positions = 55 - Grounding Contact = Without - Rows Loaded = A, B, C, E, D	Contact Related Features: - Contact Configuration = ACTION PIN Post, Signal - Feedthrough Post Length (mm [in]) = 3.71 [0.146] - CompactPCI = Yes - Contact Plating, Mating Area, Material = Gold (30) - Contact Style = Short Tail - Contact Base Material = Phosphor Bronze Housing Related Features: - Connector Style = Receptacle - Housing Material = PBT - GF - Housing Color = Gray - UL Flammability Rating = UL 94V-0 Industry Standards: - RoHS/ELV Compliance = RoHS compliant, ELV compliant - Lead Free Solder Processes = Not relevant for lead free process - RoHS/ELV Compliance History = Always was RoHS compliant Other: - Brand = AMP

BOOKMARK