







Products Industries

Resources

About TE

My Account

Innovation

Support Center

What can we help you find?

Home > Products > CHAMP Connectors > Product Feature Selector > Product Details

# 5917334-5 Product Details




Active 🖊 View 3D PDF

TE Internal Number: 5917334-5

### Product Highlights View All

- Connector Style = Header Receptacle
- 36 Positions
- · Applies To Printed Circuit Board
- Vertical Mount Angle
- · With PCB Mount Retention



Related Products

you're looking for?


**Find Similar Products** 

View Part in Product **Feature Selector** 

Check for Tooling

Not quite the product

H Feedback



| PCB Mount Retention                        | With            |
|--|-----------------|
| Mating Connector Lock ?                    | Without         |
| Product Series ?                           | Series II       |
| PCB Mount Retention<br>Type                | Boardlock(s)    |
| Color                                      | Black           |
| Mechanical Attachment                      | t               |
| Panel Mount Retention                      | With            |
| Termination Features                       |                 |
| Termination Post<br>Length (mm [in])       | 3.10 [0.122]    |
| Dimensions                                 |                 |
| PCB Thickness,<br>Recommended (mm<br>[in]) | 1.60 [0.063]    |
| Panel Thickness (mm<br>[in])               | 2.01 [0.079]    |
| <b>Body Features</b>                       |                 |
| Shell Material                             | Steel           |
| Shell Plating                              | Nickel          |
| Contact Features                           |                 |
| Contact Plating, Mating<br>Area, Material  | Gold (12)       |
| Contact Base Material                      | Phosphor Bronze |
| Solder Tail Contact<br>Plating             | Tin over Nickel |

| Configuration Features          |   |
|---------------------------------|---|
| Number of Positions ?           | 36  |
|                                 |   |
| Industry Standards              |   |
| RoHS/ELV Compliance             | RoHS compliant, ELV compliant   |
| Lead Free Solder<br>Processes ? | Wave solder capable to<br>260°C, Wave solder<br>capable to 240°C, Wave<br>solder capable to 265°C |
| RoHS/ELV Compliance<br>History  | Always was RoHS compliant   |
| UL Flammability Rating          | UL 94V-0  |
| Conditions for Usage            |   |
| Applies To ?                    | Printed Circuit Board   |
|                                 |   |
| Other                           |   |
|                                 | AMP   |

#### Corporate Information

Global Accessibility Statement

About TE Investors News Room Supplier Portal Careers Terms & Conditions

Privacy Policy

### Quick Links

Distributor Inventory Product Cross Reference Documents & Drawings

Product Compliance Support Center Site Map

## Customer Support

Email or Chat With Us Find a Phone Number Knowledge Base Manage Your Account

#### Keep Me Informed

