



Have a Question?
Chat with a Product
Information Specialist

What can we help you find?

- Products | Industries | Resources | About TE | My Account | Innovation | Support Center

Home > Products > Board-to-Board Connectors > Product Feature Selector > Product Details

826925-2 Product Details

Share Print Email

826925-2

TE Internal Number: 826925-2

Active

View 3D PDF

.100 inch AMPMODU Headers

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Header Type = Breakaway
- 4 Positions
- Mating Post Length = 6.70 mm
- Row-to-Row Spacing = 2.54 mm

[View all Features](#)

Quick Links

- Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
Product Drawings: AMPMODU II STIFTLASTE ZWEIREIHIG (PDF, English) Catalog Pages/Data Sheets: - None Available Product Specifications: - None Available Application Specifications: - None Available Instruction Sheets: - None Available CAD Files: (CAD Format & Compression Information) 2D Drawing (DXF, Version O) 3D Model (IGES, Version O) 3D Model (STEP, Version O)	Additional Information: Product Line Information Related Products: Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: - Product Type = Connector - Mount Angle = Vertical - PCB Mount Retention = Without - Surface Mount Compatible = No - Board Standoff = Without - Mating Connector Lock = Without - Profile = Standard Mechanical Attachment: - Mounting Ears = Without - Panel Mount Retention = Without Termination Features: - Termination Post Length (mm [in]) = 3.20 [0.126] - Solder Tail Contact Plating = Tin Dimensions: - Mating Post Length (mm [in]) = 6.70 [0.264] Body Features: - Header Type = Breakaway - Row-to-Row Spacing (mm [in]) = 2.54 [0.100] - Selectively Loaded = No - Mount Type = Printed Circuit Board	Contact Features: - Contact Plating, Mating Area, Material = Tin - Contact Base Material = Brass Housing Features: - Housing Material = Thermoplastic - GF - UL Flammability Rating = UL 94V-0 Configuration Features: - Number of Positions = 4 - Number of Rows = 2 Industry Standards: - RoHS/ELV Compliance = RoHS compliant, ELV compliant - Lead Free Solder Processes = Wave solder capable to 260°C, Wave solder capable to 240°C, Wave solder capable to 265°C - RoHS/ELV Compliance History = Always was RoHS compliant Conditions for Usage: - High Temperature Housing = No Operation/Application: - High Speed Serial Data Connector = No Other: - Brand = AMP

Corporate Information

- About TE
- Investors
- News Room
- Supplier Portal
- Careers
- Terms & Conditions
- Privacy Policy

Quick Links

- Distributor Inventory
- Product Cross Reference
- Documents & Drawings
- Product Compliance Support Center
- Site Map

Customer Support

- Email or Chat With Us
- Find a Phone Number
- Knowledge Base
- Manage Your Account

Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address