

**Live Product Chat** US Only
8:30am - 5pm ET, Mon - Fri

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)



 Active

Always EU RoHS/ELV Compliant (Statement of Compliance)

? Receptacle
? Tab Fit = 6.35 x 0.81 mm
? Line = Mark I
? Receptacle Style = Straight
? Wire Range = 3.00 - 6.00 ² [12-10] mm
[AWG]

[View all Features](#) | [Find Similar Products](#)

Product Drawings:

- ? [terminal Ip](#) (PDF, English)

? None Available

[1-Position, Positive Lock Connector](#) (PDF, English)

? [JAPANESE](#) (PDF, English)

? None Available

- ? 2D Drawing (DXF, Version O2)
- ? 3D Model (IGES, Version O2)
- ? 3D Model (STEP, Version O2)

List all Documents

? Product Line Information

? Tooling

Product Type Features:

- ? Product Type = Receptacle
- ? Tab Fit (mm [in]) = 6.35 x 0.81 [.250 x .032]
- ? Receptacle Style = Straight
- ? Insulation Diameter (mm [in]) = 3.78 -4.90
[.149 -.192]
- ? Material = Brass
- ? Finish = Tin
- ? Keyed = No

? Wire Range (mm [AWG]) = 3.00 -6.00 ² [12-10]
 ? Position Keyed = None
 ? Stock Thickness (mm [in]) = 0.38 [0.015]

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Not relevant for lead free process
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? Packaging Method = Loose Piece

- ? Line = Mark I
- ? Brand = AMP