

 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri

 Active

Always EU RoHS/ELV Compliant (Statement of Compliance)

? DIP Socket
? Number of Positions = 14
? Row-to -Row Spacing = 7.87 mm
? Thru Hole
? Mount Style = Vertical

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

Product Drawings:

? None Available

? None Available

? None Available

[DIPLOMATE DL \(Dual Leaf\) DIP Sockets](#) (PDF, English)

? None Available

? None Available

List all Documents

? Product Line Information

? Tooling

Product Type Features:

- ? Product Type = DIP Socket
- ? Number of Positions = 14
- ? Profile = Standard
- ? Frame Style = Ladder
- ? Leg Style = Straight
- ? Proprietary Name = DIPLOMATE DL
- ? Color = Black
- ? Comment = ONLY sockets with straight solder tails are recommended for automatic insertion.

? Insulation Resistance (M?) = 10,000
? Contact Resistance (m?) = 30

? Termination (Solder) Post Length (mm [in]) = 3.25 [0.128]
 ? Solder Tail Contact Plating = Tin

? Row-to-Row Spacing (mm [in]) = 7.87 [0.310]

? Mount Style = Vertical

? Centerline (mm [in]) = 2.54 [0.100]

? Contact Mount = Thru Hole

? Contact Material = Phosphor Bronze

? Contact Mating Area Plating Material = Gold

(15)

? Contact Style = Stamped + Formed

? Mating Contact Type = Dual Leaf

?	Housing Material = Thermoplastic Glass Reinforced	
?	Housing Flammability Rating = UL 94V	-0

? Height Above PC Board (mm [in]) = 5.33
[0.210]

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? Temperature Range ($^{\circ}\text{C}$) = 125

? Application = Production

? Packaging Method = Tube

? Brand = Tyco Electronics