


2-640361-4 Product Details



2-640361-4

TE Part Number: 2-640361-4

Active

Add to Part List

DIP Sockets

Not EU RoHS or ELV Compliant (Find RoHS Compliant Alternates)

Product Highlights:

- DIP Socket
- Number of Positions = 24
- Row-to-Row Spacing = 15.49 mm
- Thru Hole
- Mount Style = Vertical

View all Features | Find Similar Products

Live Product Chat

Quick Links

- Check Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product
- Request Samples

NEW!

Documentation & Additional Information

Product Drawings:

- SOCKET ASSY, DIP, 24 POS, DIPLOMATE DL (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- DIPLOMATE DL (Dual Leaf) DIP Sockets (PDF, English)

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- Product Line Information

Related Products:

- Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = DIP Socket
- Number of Positions = 24
- Profile = Standard
- Frame Style = Closed
- Leg Style = Straight
- Proprietary Name = DIPLOMATE DL
- Color = Black
- Qty./Tube = 17
- Qty. Tubes/Box = 100
- Product Series = Standard
- Comment = ONLY sockets with straight solder tails are recommended for automatic insertion.

Electrical Characteristics:

- Insulation Resistance (MΩ) = 10,000
- Contact Resistance (mΩ) = 30

Termination Related Features:

- Termination (Solder) Post Length (mm [in]) = 3.25 [0.128]

Body Related Features:

- Row-to-Row Spacing (mm [in]) = 15.49 [0.610]
- Mount Style = Vertical
- Centerline (mm [in]) = 2.54 [0.100]

Contact Related Features:

- Contact Mount = Thru Hole
- Contact Material = Phosphor Bronze
- Contact Mating Area Plating Material = Gold (15)
- Contact Style = Stamped + Formed
- Mating Contact Type = Dual Leaf

Housing Related Features:

- Housing Material = Thermoplastic Glass Reinforced
- Housing Flammability Rating = UL 94V-0

Configuration Related Features:

- Height Above PC Board (mm [in]) = 5.33 [0.210]

Industry Standards:

- RoHS/ELV Compliance = Not ELV/RoHS compliant
- Lead Free Solder Processes = Wave solder capable to 240°C

Conditions for Usage:

- Temperature Range (°C) = 125

Operation/Application:

- Application = Production

Packaging Related Features:

- Packaging Method = Tube

Other:

- Brand = AMP