


 [Live Product Chat](#)



✓ Active

 [Add to Part List](#)

 Always EU RoHS/ELV Compliant (Statement of Compliance)

- Header
- Header Type = Breakaway
- Number of Rows = Single
- Number of Positions = 4
- Mating Post Length = 5.84 mm

[View all Features](#) | [Find Similar Products](#)

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

- None Available

- None Available

- None Available

- None Available

- None Available

- None Available

- Product Line Information

- Tooling

- Product Type = Header
- Number of Positions = 4
- Mount Angle = Vertical
- PCB Retention Feature = No
- Surface Mount Compatible = Yes
- Board Standoff = With
- Mounting Ears = Without
- Mating Connector Lock = Without
- Post Size (mm [in]) = 0.64 [.025]

- Mating Post Length (mm [in]) = 5.84 [0.230]
- Panel Attachment = Without

- Termination (Solder) Post Length (mm [in]) = 2.29 [0.090]
- Solder Tail Contact Plating = Tin over Nickel, Matte Tin over Nickel

- Header Type = Breakaway
- Number of Rows = Single
- Centerline, Matrix (mm [in]) = 2.54 [.100]
- Selectively Loaded = No
- Mount Type = PC Board

- Contact Mating Area Plating Material = Gold (30)
- Contact Shape = Square
- Contact Material = Phosphor Bronze

- Housing Material = Liquid Crystal Polymer (LCP)
- Housing Flammability Rating = UL 94V-0

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

- High Temperature Housing = Yes

- High Speed Serial Data Connector = No

- Brand = AMP