

PCB D-SUB CONNECTORS



✓ Active

TE CONNECTIVITY (TE)

CHAMP.050 REC ASS'Y 26P PB-FREE

CHAMP | .050 CHAMP Series II

5178238-4

TE Internal Number: 5178238-4

EU RoHS Compliant

EU ELV Compliant

Connector Style Receptacle

Number of Positions 26

Centerline (Pitch) 1.27 mm [.05 in]

Number of Rows 2

Row-to-Row Spacing .05



PRODUCT DRAWING

English



→ 3D PDF

DOCUMENTATION

Product Drawings

RECEPTACLE HDR ASSY (3.1mm) RETENTION LEG TYPE STANDARD CHAMP.050 SERIES (II)

PDF

English

CAD Files

Customer View Model

2D_DXF.ZIP

English

3D PDF

PDF

3D

Customer View Model 3D_IGS.ZIP **English Customer View Model** 3D_STP.ZIP **English Product Specifications Product Specification CHAMP.050 Series(II) Connector Wire To Board Type** TIF **English** CHAMP.050 Series(II) Connector Wire To Board Type PDF **English FEATURES** Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity. **Product Type Features Shell Type** Front Metal Shell **Connector Style** Receptacle Row-to-Row Spacing .05 **Profile Standard PCB Mounting Orientation** Vertical Connector & Contact Terminates To Printed Circuit Board **Product Type** Connector **Connector Type** Header **Configuration Features Number of Positions 26** Number of Rows 2 **Preloaded** Yes **Body Features Shell Plating Material** Nickel **Shell Material** Steel Color Black Tine Plate Material Thermoplastic **Contact Features** Solder Tail Contact Plating Material Tin Contact Mating Area Plating Thickness (µin) 12

Contact Base Material Copper Alloy

Contact Mating Area Plating Material Gold

Termination Features	
Termination Post Length 3.1 mm [.122 in]	
Mechanical Attachment	
Panel Mount Feature With	
PCB Mounting Style Through Hole	
PCB Mount Retention With	
PCB Mount Retention Type Retention Legs	
Mating Connector Lock With Mating Connector Lock Type Bail Lock	
Mounting Hole Diameter (mm) 2.7	
Mounting Angle Right Angle	
Housing Features	
Centerline (Pitch) 1.27 mm [.05 in]	
Housing Color Black	
Housing Material Zinc Die Cast	
Dimensions	
PCB Thickness (Recommended) (mm) 1.6	
Usage Conditions	
Housing Material Temperature Standard	
Industry Standards	
UL Flammability Rating UL 94V-0	
Packaging Features	
Packaging Quantity 120	
Packaging Method Tray	
PRODUCT COMPLIANCE	+
Statement of Compliance	
Statement of Compliance PDF	