


 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



 Active

Always EU RoHS/ELV Compliant (Statement of Compliance)

- ? Type C Connectors
- ? Receptacle
- ? Number of Positions = 96
- ? Rows Loaded = A, B, C
- ? Terminate To Printed Circuit Board

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[View Mating Products \(21\)](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

Product Drawings:

- [ASSEMBLY, RECEPTACLE EUROCARD, TYPE C, 96 POSITION, ...](#)
(PDF, English)

? None Available

? None Available

[Eurocard Connectors Types B,C,M,Q,R, & Enhanced Typ... \(PDF, English\)](#)

? None Available

? None Available

List all Documents

? Product Line Information

? Tooling

? Mating Products (21)

Product Type Features:

- ? Product Type = Type C Connectors
 ? Gender = Receptacle
 ? Number of Positions = 96
 ? PCB Retention Feature = Yes
 ? PCB Mount Angle = Vertical
 ? PCB Thickness (Minimum) (mm [in]) = 1.57
 [0.062]
 ? Post Type = Compliant Post
 ? Size = Standard
 ? Make First / Break Last = No
 ? Bus Type = FUTUREBUS, MULTIBUS (II),
 NUBUS, VMEbus, VXIBus
 ? DIN Level = II
 ? Mounting Ears = Without
 ? Toolless (Flat Rock) = Yes
 ? Color = Gray

? Termination (Solder) Post Length (mm [in]) = 4.83 [0.190]
? Solder Tail Contact Plating = Tin

? Rows Loaded = A, B, C

? PCB Retention Method = ACTION (Compliant)
Press-fit Posts

? Contact Cross Section (mm [in]) = 0.30 x 0.61
[.012 x .024]

? Contact Material = Copper Alloy

? Contact Mating Area Plating Material = DIN 41612 Class 2

? Housing Flammability Rating = UL 94V -0

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Not relevant for lead free process
- ? Flux - Tight Coating = Without
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? Terminate To = Printed Circuit Board

? High Temperature Housing = No

? Brand = AMP