

 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



Always EU RoHS/ELV Compliant (Statement of Compliance)

? Mating Type = Plug
? Number of Positions = 64
? PCB Mount Angle = Right Angle
? Post Type = Solder Post
? Not Make First / Break Last

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

List all Documents

Product Line Information

? Tooling

- ? Mating Type = Plug
- ? Number of Positions = 64
- ? PCB Mount Angle = Right Angle
- ? Post Type = Solder Post
- ? Make First / Break Last = No
- ? Bus Type = CIMBUS, STE Bus
- ? DIN Level = II
- ? Size = Standard
- ? PCB Retention Feature = Yes
- ? PCB Thickness (Minimum) (mm [in]) = 1.57
[0.062]
- ? Color = Gray

? Termination (Solder) Post Length (mm [in]) = 2.65 [0.104]

? Contact Cross Section (mm [in]) = 0.64 [.025]
Sq.
? PCB Retention Method = Boardlock(s)
? Rows Loaded = A, B

? Contact Material = Brass

?	Housing Material = Polyester	
?	Housing Flammability Rating = UL 94V	-0

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? Flux - Tight Coating = Without
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? Terminate To = Printed Circuit Board

? Brand = AMP