


5557564-1 Product Details

 Share

 Print

 Email



5557564-1

TE Internal Number: 5557564-1

 Active

PCB Mounted Jacks - Single Port, Multi-port and Stacked

 Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Preloaded
- Multiple Port Configuration
- 1 x 6 Jack Configuration
- Jack Type = RJ45

[View all Features](#)

Quick Links

- Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information	
Product Drawings: MODULAR JACK ASSEMBLY, SIX PORT, 8 POSITION, RIGHT ANGLE (PDF, English) Catalog Pages/Data Sheets: - None Available Product Specifications: High Performance Modular Plugs & Jacks, PCB Mounted (PDF, English) Application Specifications: Modular Jacks (PDF, English) Instruction Sheets: - None Available CAD Files: - None Available Additional Information: Product Line Information Related Products: Tooling	List all Documents

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: - Product Type = Connector - Jack Type = RJ45 - PCB Mounting Orientation = Side Entry (Right Angle) - PCB Mount Style = Through Hole - Termination Method to PC Board = Solder - Performance Category = Cat 3 - LED = Without - Grounding Options = Without - Panel Stops = Without - Keyed = No - Profile = Standard - Color = Black Mechanical Attachment: - Panel Mount Retention = Without Electrical Characteristics: - Shielded = No Termination Features: - Solder Tail Contact Plating = Tin over Nickel Dimensions: - PCB Tail Length (mm [in]) = 3.56 [0.140] Body Features: - Inverted Jack Face = No - Number of Contacts Loaded, RJ45 (8 Positions) = 8 Contact Features: - Contact Plating, Mating Area, Material = Gold (50) - Contact Base Material = Phosphor Bronze Housing Features: - Housing Material = High Temperature Nylon - UL Flammability Rating = UL 94V-0 Configuration Features: - Preloaded = Yes - Port Configuration = Multiple - Jack Configuration = 1 x 6 - Number of Positions = 8 - Number of Contacts Loaded = 8 Industry Standards: - RoHS/ELV Compliance = RoHS compliant, ELV compliant - Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C - RoHS/ELV Compliance History = Always was RoHS compliant Packaging Features: - Packaging Method = Tray - Packaging Quantity = 15 Product Availability: - Region = Asia, North America Other: - Brand = AMP - Comment = On any modular jack, Terminal No. 1 is the terminal to the extreme left as you face the jack opening, tab notch down.	

Corporate Information

[About TE](#)

[Investors](#)

[News Room](#)

[Supplier Portal](#)

[Careers](#)

[Terms & Conditions](#)

[Privacy Policy](#)

Quick Links

[Distributor Inventory](#)

[Product Cross Reference](#)

[Documents & Drawings](#)

[Product Compliance Support Center](#)

[Site Map](#)

Customer Support

[Email or Chat With Us](#)

[Find a Phone Number](#)

[Knowledge Base](#)

[Manage Your Account](#)

Keep Me Informed

