

 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



Eurocard Type C

Always EU RoHS/ELV Compliant (Statement of Compliance)

? Type C Connectors
? Receptacle
? Number of Positions = 150
? Rows Loaded = A, B, C
? Terminate To Printed Circuit Board

[View all Features](#) | [Find Similar Products](#)

Quick Links

[Check Pricing & Availability](#)

[Search for Tooling](#)

[View Mating Products \(4\)](#)

[Product Feature Selector](#)

[Contact Us About This Product](#)

Documentation & Additional Information

[ASSEMBLY, RECEPTACLE, EUROCARD, TYPE C, LEAD -FREE, 1...](#)
(PDF, English)

? None Available

? None Available

[Eurocard Connectors Types B,C,M,Q,R, & Enhanced Typ... \(PDF, English\)](#)

? None Available

- ? 2D Drawing (DXF, Version O)
- ? 3D Model (IGES, Version O)
- ? 3D Model (STEP, Version O)

Product Line Information

? Tooling

? Mating Products (4)

List all Documents

Product Features

- ? Product Type = Type C Connectors
- ? Gender = Receptacle
- ? Number of Positions = 150
- ? PCB Retention Feature = No
- ? PCB Mount Angle = Vertical
- ? Post Type = Solder Post
- ? Size = Expanded
- ? Make First / Break Last = No
- ? DIN Level = II
- ? Mounting Ears = With
- ? Toolless (Flat Rock) = No
- ? Color = Gray

? Termination (Solder) Post Length (mm [in]) = 3.30 [0.130]
? Solder Tail Contact Plating = Tin

? Rows Loaded = A, B, C

? Contact Cross Section (mm [in]) = 0.30 x 0.61
[.012 x .024]

? Contact Material = Copper Alloy

? Contact Mating Area Plating Material = DIN 41612 Class 2

? Housing Material = Polymer

? Housing Flammability Rating = UL 94V -0

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? Flux - Tight Coating = Without
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? Terminate To = Printed Circuit Board

? High Temperature Housing = No

? Brand = AMP