


 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



 Active

Always EU RoHS/ELV Compliant (Statement of Compliance)

- ? Type C Connectors
- ? Plug
- ? Number of Positions = 150
- ? Rows Loaded = A, B, C
- ? Terminate To Printed Circuit Board

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)

[Search for Tooling](#)

[View Mating Products \(4\)](#)

[Product Feature Selector](#)

[Contact Us About This Product](#)

Product Drawings:

[ASSEMBLY, PIN, EUROCARD, TYPE C, 150 POSITION, 2.64\[... \(PDF, English\)](#)

? None Available

? None Available

[Eurocard Connectors Types B,C,M,Q,R, & Enhanced Typ... \(PDF, English\)](#)

? None Available

? None Available

List all Documents

? Product Line Information

? Tooling

? Mating Products (4)

(Please use the Product Drawing for all design activity)

? Product Type = Type C Connectors

? Gender = Plug

? Number of Positions = 150

? PCB Retention Feature = Yes

? PCB Mount Angle = Right Angle

? Post Type = Solder Post

? Size = Expanded

? Make First / Break Last = No

? DIN Level = II

? Mounting Ears = With

? Guides = Without

? Toolless (Flat Rock) = No

? Color = Gray

? Termination (Solder) Post Length (mm [in]) = 2.65 [0.104]
 ? Solder Tail Contact Plating = Tin

? Rows Loaded = A, B, C

? PCB Retention Method = Boardlock(s)

? Contact Cross Section (mm [in]) = 0.64 [.025]

Sq.

? Contact Material = Copper Alloy

? Contact Mating Area Plating Material = DIN 41612 Class 2

? Housing Material = Polymer

? Housing Flammability Rating = UL 94V -0

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? Flux - Tight Coating = Without
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? Terminate To = Printed Circuit Board
? High Temperature Housing = No

? Brand = AMP