



What can we help you find?



Email

Products

Industries

Resources

About TE My Account

Always EU RoHS/ELV Compliant (Statement of Compliance)


Innovation

Support Center

Share

Home > Products > Ribbon Cable Interconnects > Product Feature Selector > Product Details

5746443-8 Product Details



5746443-8

AMP-LATCH Pin and Pinless Headers

Product Highlights:

- Header
- Header Type = Universal Ejection Pin Headers
- AMP-LATCH Product Line
- Standard Profile
- 34 Positions

View all Features

Quick Links-

- Pricing & Availability Search for Tooling
- View Mating Products (5)
- Product Feature Selector

Contact Us About This Product

Print

TE Internal Number: 5746443-8 Active













Documentation & Additional Information

Product Drawings:

HEADER ASSY, UNIVERSAL, AMP-LATCH (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

AMP-LATCH ACTION PIN Header Connector (PDF, English)

Application Specifications:

AMP-LATCH Universal Headers with ACTION PIN Contacts (PDF, English)

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version D)
- 3D Model (IGES, Version D)
- 3D Model (STEP, Version D)

Additional Information:

Product Line Information

Related Products:

- Tooling
- Mating Products (5)

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Connector Type = Header
- Product Line = AMP-LATCH
- Profile = Standard
- PCB Mounting Orientation = Vertical
- PCB Mount Retention = With
- PCB Mount Retention Type = Action/Compliant Tail
- Mating Connector Lock = With
- Ejection Latches = With
- Post Size (mm [in]) = 0.64 [.025]
- Shrouded = Yes
- Latch Type = Long
- Mating Connector Lock Type = Latch

Termination Features:

- Termination Post Length (mm [in]) = 4.42 [0.174]
- Solder Tail Contact Plating = Tin

Dimensions:

PCB Thickness, Recommended (mm [in]) = 1.57 [0.062]

Body Features:

Header Type = Universal Ejection Pin Headers

Contact Features:

- Contact Plating, Mating Area, Material = Gold (30)
- Contact Shape = Square

Housing Features:

- Centerline, Matrix (mm [in]) = 2.54 x 2.54 [.100 x .100]
- Mating Alignment Type = Center & Dual, Military
- Housing Style = 4-Sided
- · Mating Alignment = With
- Housing Material = Nylon
- UL Flammability Rating = UL 94V-0
- Housing Color = Black

Configuration Features:

Number of Positions = 34

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

Temperature Rating = Standard

Other:

- Brand = AMP
- Comment = Pin headers in 10- and 14-position sizes have only one slot for snap-in polarizer (military polarization), located as shown.

Corporate Information

About TE Investors News Room Supplier Portal Careers

Distributor Inventory Product Cross Reference Documents & Drawings

> Product Compliance Support Center Site Map

Quick Links

Customer Support Email or Chat With Us Find a Phone Number Knowledge Base Manage Your Account

Keep Me Informed

Receive TE News, Events & Technology Updates













