

 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



Discrete Sockets

Not reviewed for RoHS Compliance

- Socket
- Mating Pin Dia. Range = .51 - .66 mm
- Socket Length = 4.01 mm
- Sleeve Style = Bullet Nose
- Tin Sleeve Plating

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

Product Drawings:

- None Available

- None Available

- None Available

- [Miniature Spring Socket On Polyester Strips](#) (PDF, English)

- None Available

- None Available

List all Documents

- Product Line Information

- Tooling

Product Type Features:

- Product Type = Socket
- Socket Length (mm [in]) = 4.01 [0.158]
- Sleeve Style = Bullet Nose
- Sealant = Without
- Sleeve Material = Copper
- Recommended Hole Size (mm [in]) = 1.32 [0.052]

- Mating Pin Dia. Range (mm [in]) = 0.51 – 0.66
[0.020 – 0.026]
- Spring Material = Beryllium Copper

- Sleeve Plating = Tin
- Contact Spring Plating = Gold (30)
- Contact Material = Beryllium Copper

- Insertion Method = Hand/Semi-Automatic/Automatic

- Government/Industry Qualification = No
- [RoHS/ELV Compliance](#) = Not reviewed for ELV/RoHS compliance
- [Lead Free Solder Processes](#) = Not reviewed for lead free solder process

- Application = Production

- Packaging Method = Carrier Tape
- Packaging Quantity = 50,000/Reel

- Brand = AMP