

A perspective view of a square connector with a cylindrical cap. The connector has a square body with a recessed slot on one side. The cap is cylindrical with a flared base and a textured top surface.

 Active

Always EU RoHS/ELV Compliant (Statement of Compliance)

- Tab
- Proprietary Name = Ultra-Fast
- Tab Fit = 6.35 x 0.81 mm
- Brass Material
- Insulation Diameter = 3.43 [.135]
Max. mm [in]

[View all Features](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

- [TAB ASSEMBLY, ULTRA-FAST, LOOSE PIECE, .250 SERIES, 22-1...](#)
(PDF, English)

- [FASTON TERMINALS \(INSULATED & UNINSULATED\)](#) (PDF, English)

- [Terminal, FASTON, Tab, Ultra-Fast Fully Insulated](#) (PDF, English)

- [Ultra-Fast Series 110, 125, 187, 205, and 250 Fully-... \(PDF, English\)](#)

- None Available

- 3D Model (STEP)
- 3D Model (IGES)
- 2D Drawing (DXF)

List all Documents

- Product Line Information

- Tooling

- Product Type = Tab
- Proprietary Name = Ultra-Fast
- Tab Fit (mm [in]) = 6.35 x 0.81 [.250 x .032]
- Material = Brass
- Insulation Diameter (mm [in]) = 3.43 [.135]
Max.
- Insulation Support = Non-Insulation Support
- Industry Application = Standard
- Finish = Tin
- Wire/Cable Type = Regular Wire
- Mount Angle = Straight

- Wire Range (mm [AWG]) = 0.30-0.90² [22-18]
- Tab Type = Wire Crimp
- Fully Insulated = Fully Insulated

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

- Packaging Method = Loose Piece

- Brand = AMP