

Connectors > Audio & Video Connectors > SAS & MiniSAS > SAS

12G SAS REC RIGHT ANGLE CONNECTOR



SAS

TE Part # **2309567-1**
TE Internal #: **2309567-1**

Connector Style : **Receptacle**
Connector System : **Board-to-Board**
Number of Positions : **68**
Number of Rows : **2**
PCB Mounting Style : **Surface Mount**

[Similar Products](#)

ORDER SAMPLES

Compatible Parts & Tooling

SHOP OUR DISTRIBUTORS

North America

See all price breaks

Distributor	1	10,000	Buy
MOUSER ELECTRONICS	\$9.590	\$6.190	SHOP NOW
1,239 in stock			
ONLINE COMPONENTS	\$12.260	\$5.310	SHOP NOW
250 in stock			
NEWARK ELEMENT14	\$10.450	\$7.960	Visit Site
250 in stock			

We are here to help!

Get in touch with our product experts.

CHAT WITH US

EMAIL US

CALL US

DOCUMENTSFEATURESPRODUCT COMPLIANCE

Product Drawings

12G SAS REC RIGHT ANGLE CONNECTOR

12G SAS REC RIGHT ANGLE CONNECTOR

English

CAD Files

3D PDF

3D_CVM_CVM_2309567-1_1.pdf

3D

Customer View Model

ENG_CVM_CVM_2309567-1_1.2d_dxf.zip

English

ENG_CVM_CVM_2309567-1_1.3d_igs.zip

English

ENG_CVM_CVM_2309567-1_1.3d_stp.zip

English

Product Specifications

Application Specification

ENG_SS_114-60017_A.pdf

English

Product Specification

ENG_SS_108-51109_A1.pdf

English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Feedback



Product Type Features	Shell : Without Connector Style : Receptacle Connector System : Board-to-Board Connector & Contact Terminates To : Printed Circuit Board Product Grouping : SAS Product Type : Connector
Configuration Features	Stackable : No Number of Positions : 68 Number of Rows : 2 PCB Mount Orientation : Right Angle Key Type : SAS Keyed : No Plug Configuration : SAS
Contact Features	Contact Base Material : Copper Alloy Contact Current Rating (Max) (A): 1.5 Contact Mating Area Plating Material : Gold Contact Mating Area Plating Thickness (µin): 30
Mechanical Attachment	PCB Mount Retention Type : Solder Peg PCB Mount Retention : With PCB Mounting Style : Surface Mount
Housing Features	Housing Color : Black Housing Material : LCP (Liquid Crystal Polymer)
Usage Conditions	Operating Temperature Range : 0 – 55 °C [0 – 131 °F] High Temperature Housing : Yes
Operation/Application	Circuit Application : Signal
Industry Standards	UL Flammability Rating : UL 94V-0

Statement of
Compliance

[Statement of Compliance pdf](#)

Also in the Series | [SAS](#)



Heat Shrink Tubing (6)



Mini-SAS Cages (1)



Mini-SAS Connectors
(1)



Pluggable I/O Cable
Assemblies (142)

Need help?

Our team is on stand-by and ready to help with your order.

[CHAT NOW](#)



ABOUT TE CONNECTIVITY

[Our Company](#)
[Events](#)
[TE News Center](#)
[Careers](#)
[Investors](#)
[Corporate Responsibility](#)
[Terms and Conditions of Sale](#)

FOR PARTNERS

[Distributors](#)
[Suppliers](#)

SUPPORT

[Customer Service](#)
[Find Authorized Distributors](#)
[Shop Online in the TE Store](#)
[Product FAQs](#)

CALL US

LOCATIONS

[United States](#)
[Germany \(DE\)](#)
[China \(中文\)](#)
[Japan \(日本語\)](#)

[Afghanistan \(EN\)](#)

[Find Your Country/Region](#)

[Terms of Use](#) | [Privacy](#) | [Cookie Policy](#) | [Accessibility](#) | [Site Map](#) |

© 2018 TE Connectivity. All Rights Reserved.

