



✓ Active

 Add to Part List

Always EU RoHS/ELV Compliant (Statement of Compliance)

- Socket
- Contact Type = Receptacle
- Wire Range = 0.20-0.40² [24-22] mm [AWG]
- 2.54 mm Centerline
- Wire/Cable Type = Round Wire, Discrete

[View all Features](#) | [Find Similar Products](#)

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [View Housings \(94\)](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)
- ▶ [Request Samples](#)

- [CONTACT, RCPT., ROUND WIRE, .100CL FFC \(PDF, English\)](#)

- None Available

- None Available

- [FFC Round Wire Pin and Receptacle Contacts](#) (PDF, English)
- [Flexible Flat Cable \(FFC\) Housings with Contact Cavi...](#) (PDF, English)

- [Application and Maintenance for Hand Crimping Tool](#) (PDF, English)

- None Available

- Product Line Information

- Tooling
- Housings (94)

List all Documents

- Pin/Socket = Socket
- Wire/Cable Type = Round Wire, Discrete
- Wire Insulation Diameter (mm [in]) = 1.02 – 1.42 [0.040 – 0.056]
- Comment = Use Extraction Tool No. 91092-1 for end locking slot and Extraction Tool No. 91093-1 for side locking lance slot.

- Solder Tail Contact Plating = Gold Flash

- Wire Range (mm [AWG]) = 0.20-0.40² [24-22]
- Centerline (mm [in]) = 2.54 [0.100]

- Contact Type = Receptacle
- Contact Mating Area Plating Material = Gold (15)
- Contact Underplating = Nickel (50)

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

- Packaging Method = Loose Piece

- Brand = AMP