

#### **TERMINAL BLOCKS**



✓ Active

TE CONNECTIVITY (TE)

# 1.5MM^2,1 IN 1 OUT SPRING TERMINAL BLOCK

Ultra-Pod FASTON Receptacles & Tabs

2271552-2

TE Internal Number: 2271552-2

## **EU RoHS Compliant EU ELV Compliant**

Terminal Block Type Spring Terminal Block

Centerline (Pitch) 4.15 mm [.163 in]

**Operating Temperature Range (°C)** -40 – 105

**Connector Mounting Type** DIN Rail

**Block Type** Standard



**PRODUCT DRAWING** 

English



**★** 3D PDF

### **DOCUMENTATION**

**Product Drawings** 

# 1.5mm<sup>2</sup>,1 In And 1 Out Spring Clamp Type Terminal Block

**English** 

**CAD Files** 

#### **3D PDF**

PDF

3D

## **Customer View Model**

2D\_DXF.ZIP

**English** 

**Customer View Model** 

Customer View Model 3D_STP.ZIP English  Product Specifications  Product Specification			
		Product Specification For Spring Terminal Block Connector	
		PDF	
		English	
Application Specification			
Application Specification For Spring Terminal Block Connectors  PDF			
English			
FEATURES	+		
Places review and lest decriments or contact up for the letest exercise and exercise			
Please review product documents or contact us for the latest agency approval information.  Please Note: Use the Product Drawing for all design activity.			
Product Type Features			
Terminal Block Type Spring Terminal Block			
Block Type Standard Product Type Terminal Block			
Product Type Terminal Block			
Configuration Features			
Number of Circuits 1			
Ground Function Without			
Fuse Function Without Switch Function Without			
Number of Contacts 1			
Electrical Characteristics			
Current Rating (A) 15			
Voltage Rating (VAC) 600			
Continuous Current Rating (A) 15			
Contact Features			
Contact Configuration Quick Connect			
Contact Plating Material Matte Tin  Contact Base Material Copper			
Mechanical Attachment			
Connector Mounting Type DIN Rail			

3D\_IGS.ZIP

Housing Features

Centerline (Pitch) 4.15 mm [.163 in]

Housing Color Blue

Housing Material Nylon

Dimensions

Wire Size 28 – 14 AWG [.08 – 1.5 kcmil]

Usage Conditions

Operating Temperature Range (°C) -40 – 105

Industry Standards

UL Flammability Rating UL 94V-0

Statement of Compliance

**Statement of Compliance** 

PDF