


2-1825910-6 Product Details

 Share Print Email



Pushbutton Switches

☐ Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Switch
- Tactile
- Single Pole - Single Throw Configuration (Pole-Throw)
- Contact Rating = 50mA
- Operating Function = Off [On]

[View all Features](#)

Quick Links

- Check Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

TE Internal Number: 2-1825910-6

☐ Active

[View 3D PDF](#)

[Add to My Part List](#)  [Request Sample](#)  [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
Product Drawings: 6MM TACT SWITCH, THRU-HOLE HIGH TEMP (PDF, English) Catalog Pages/Data Sheets: SWITCHES_CORE_PROGRAM_CATALOG (PDF, English) Product Specifications: - None Available Application Specifications: - None Available Instruction Sheets: - None Available CAD Files: (CAD Format & Compression Information) 2D Drawing (DXF, Version C) 3D Model (IGES, Version C) 3D Model (STEP, Version C)	Related Products: Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: - Product Type = Switch - Tactile = Yes - Configuration (Pole-Throw) = Single Pole - Single Throw Series = FSM - Mount Angle = Vertical - Termination Type = Printed Circuit - Actuator Style = Round Electrical Characteristics: - Contact Rating = 50mA Body Features: - Mount Style = Through-Hole - Actuator Length (mm [in]) = 9.40 [0.370] - Actuator Profile = Extended - Actuator Color = Brown - Case Material = Nylon - Actuator Material = Nylon Contact Features: - Contact Plating = Silver Housing Features: - Process Sealed = No - Low Profile = No	Configuration Features: - Operating Function = Off [On] - Ganged = No - ESD Grounding Terminal = Without - Actuator Force (g [oz]) = 100.00 [3.530] - Number of Actuators = Single - Illuminated = No - Dust Proof = No - Support Bracket = Without - Snap Action = Without Industry Standards: RoHS/ELV Compliance = RoHS compliant, ELV compliant Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C - RoHS/ELV Compliance History = Always was RoHS compliant Conditions for Usage: - Temperature Rating = High Packaging Features: - Packaging Method = Loose Piece Other: - Brand = Alcoswitch - Comment = (On) indicates momentary position.