


 [Live Product Chat](#)



 [Add to Part List](#)

 Always EU RoHS/ELV Compliant (Statement of Compliance)

- Switch - Mechanical
- Not Tactile
- Single Pole - Single Throw Configuration (Pole-Throw)
- Contact Rating = 0.4VA
- Process Sealed

[View all Features](#) | [Find Similar Products](#)

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Product Drawings:

- [SEALED PUSHBUTTON SWITCH SINGLE POLE, TSP SERIES, RO...](#)
(PDF, English)

- None Available

- None Available

- None Available

- None Available

- 2D Drawing (DXF, Version A)
- 3D Model (IGES, Version A)
- 3D Model (STEP, Version A)

- Product Line Information

- Tooling

[List all Documents](#)

Product Type Features:

- Product Type = Switch - Mechanical
- Tactile = No
- Configuration (Pole-Throw) = Single Pole - Single Throw
- Mount Angle = Vertical
- Termination Type = Printed Circuit
- Actuator Style = Round
- Comment = (On) indicates momentary position.; Omit center terminal.; Off indicates a mechanical position with no electrical connection.

- Contact Rating = 0.4VA

- Series = TSP
- Mount Style = Surface Mount
- Actuator Length (mm [in]) = 5.08 [0.200]
- Actuator Profile = Extended
- Actuator Color = Black
- Case Material = Thermoplastic (LCP)
- Actuator Material = Glass reinforced nylon

- Contact Plating = Gold over Nickel
- Contact Material = Copper Alloy

- Process Sealed = Yes
- Low Profile = No

- Operating Function = Off [On]
- Ganged = No
- ESD Grounding Terminal = Without
- Number of Actuators = Single
- Illuminated = No
- Dust Proof = No
- Support Bracket = Without
- Snap Action = Without

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

- Temperature Rating = High

- Packaging Method = Loose Piece

- Brand = Alcoswitch