

[My Cart](#) | [My Part Lists](#) | [Sign In/Register](#) | [My Account](#)[English](#) ([Change](#))Search by Keyword or Part #

UP3DTANLB04 Product Details

Have a Question?

Chat with a Product
Information Specialist**UP3DTANLB04**

TE Internal Number: 1-1825043-6

[Active](#)[View 3D PDF](#)

Snap Action Switches

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- Switch Style = Ultra Miniature
- Actuator Style = Lever, Normal
- Termination Type = Printed Circuit Board
- Single Pole - Double Throw Configuration (Pole-Throw)
- Contact Rating = 3A

[View all Features](#)

Quick Links

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)[Add to My Part List](#)[Request Sample](#)[Find Similar Products](#)[Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [SWITCH, SNAP ACTION, ULTRAMINIATURE](#) (PDF, English)

Catalog Pages / Data Sheets:

- [SWITCHES, CORE PROGRAM CATALOG](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version B1)
- [3D Model](#) (IGES, Version B1)
- [3D Model](#) (STEP, Version B1)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Actuator Style = Lever, Normal
- Termination Type = Printed Circuit Board
- Configuration (Pole-Throw) = Single Pole - Double Throw
- Mount Angle = Vertical

Mechanical Attachment:

- Operating Force (g [oz]) = 30 [1.058]

Electrical Characteristics:

- Contact Rating = 3A

Body Related Features:

- Switch Style = Ultra Miniature
- Releasing Force (g [oz]) = 5 [0.176]
- Pre Travel (mm [in]) = 3.00 [0.118]
- Operating Position (mm [in]) = 7.90 [0.311]
- Over Travel (mm [in]) = 0.60 [0.024]
- Movement Differential (mm [in]) = 0.80 [0.031]

Contact Related Features:

- Contact Base Material = Brass
- Contact Plating = Gold over Nickel

Housing Related Features:

- Housing Material = Nylon

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

- Brand = Tyco Electronics



Corporate Information

[Who We Are](#)[Investors](#)[News Room](#)[Supplier Portal](#)[Careers](#)

Quick Links

[Check Distributor Inventory](#)[Cross Reference](#)[Find Documents & Drawings](#)[Product Compliance Support Center](#)[Site Map](#)

Customer Support

[Email or Chat with Us](#)[Find a Phone Number](#)[Search Knowledge Base](#)[Manage Your Account](#)

Sign up for our eNewsletter

Enter your email address

Follow Us On:

[Twitter](#) [Facet](#) [Flickr](#) [Linke](#) [YouTi](#)

Visit Us On:



