

Material:

- Cable: UL-2725 [28AWG(7/0.127)*1PR+24AWG(7/0.203)*2C
  +AL-FOIL/MYLAR+DRAIN WIRE(7/0.127)+65% BRAID]TIN
  - OD: 4.7±0.15MM
  - PVC Jacket
  - Color: Beige
- P1 Connector: USB A Type Male
  - Gold Plated 30µ" Contact
  - Nickel Plated Shell
- P2 Connector: USB A Type Female
  - Gold Plated 30µ" Contact
  - Nickel Plated Shell
- Hood: Molded Type, PVC 45P, Color Beige
- Tooling Cavity indication for inspection

Electrical:

- 100% Open short & mis wire test
- Contact Resistance: 3Ω Max.
- Insulation Resistance: 20MΩ Min.

PIN OUT

	P1	P2	
RED	1	1	VCC
WHITE	2	2	-DATA
GREEN	3	3	+DATA
BLACK	4	4	GROUND
SHELL	BRAID		SHELL

RoHS Complaint

Scale	1:1						Name
TOLERANCE					Drawn	08.29.11	Chappell
X.X	±0.40				Approved	10.19.11	Warner
X.XX	±0.25						
X.XXX	±0.15						
Angle	±3°						
			Modification	Date	Name		

ASSMANN WSW components

Item No.
AK669/2-50-R

Title: Hi-Speed USB 2.0 Extention cable, 5 Meters, Beige, USB A Male <=> USB A Female

Drawing No.

rev00

Replace

Sheet